

Item no.: 367023

UVC-G4 Doorbell Pro PoE Kit, Premium UniFi Doorbell

from **423,24 EUR**

Item no.: 367023
shipping weight: 0.60 kg
Manufacturer: Ubiquiti

Product Description

Your premium UniFi doorbell with integrated PoE and included PoE chime for plug-and-play installation.

- Improved HDR and low-light performance
- Programmable welcome display and secondary package-detection camera
- AI event detections
- Connect and power using PoE
- Integrated 2-way audio
- Includes PoE Chime
- Weather-resistant (outdoor covered)

Mechanical

- Dimensions Device: 160.6 x 51.7 x 35.1 mm (6.3 x 2 x 1.4")
- Wall mount: 159.3 x 50.3 x 17.5 mm (6.3 x 1.9 x 0.7")
- Wedge: 161.1 x 52.1 x 25.7 mm (6.3 x 2.1 x 1")
- On-wall mount: 161.1 x 52.1 x 25.75 mm (6.3 x 2.1 x 1")
- Weight Device: 264 g (9.3 oz)
- Wall mount: 56 g (2 oz)
- Wedge: 33 g (1.2 oz)
- On-wall mount: 53 g (1.9 oz)
- Enclosure materials Aluminum alloy, polycarbonate
- Mount materials Wall mount: aluminum alloy
- Wedge: polycarbonate
- On-wall mount: polycarbonate
- Weatherproofing IPX4

Optics

- Sensor Main camera: 5MP CMOS sensor
- Package camera: 8MP CMOS sensor
- Lens Fixed focal length
- View angle Main camera: H: 138°, V: 114°, D: 155°
- Package camera: H: 97.5°, V: 79.4°, D: 118.2°
- Night mode Built-in IR LED illumination and IR cut filter

Video

- Video compression H.264
- Resolution 1600 x 1200 (4:3)
- Max. frame rate 30 FPS

System

- Processor Quad-core Arm® Cortex®-A53 based chip
- Networking interface GbE RJ45 port
- Power method PoE
- Supported voltage range 37—57V DC
- Max. power consumption 7W
- LED Link/activity
- Button (1) Ring button
- (1) Factory reset
- Operating temperature -30 to 40° C (-22 to 104° F)
- Operating humidity 10 to 90% noncondensing
- Certifications CE, FCC, IC

Audio

- Microphone Yes (Can be disabled)
- Speaker Yes

Software

- UniFi OS application UniFi Protect
- Mobile app UniFi Protect iOS™ and Android™

UP-Chime PoE Mechanical

- Dimensions Device: Ø62 x 54 mm (Ø2.5 x 2.1")
- In-wall mount: Ø89 x 63.1 mm (Ø3.5 x 2.5")
- On-wall Mount: Ø62 x 20.2 mm (Ø2.5 x 0.8")
- Weight Device: 158 g (5.6 oz)
- In-wall mount: 91 g (3.2 oz)
- On-wall mount: 28 g (1 oz)
- Enclosure materials Aluminum alloy, polycarbonate
- Mount materials Polycarbonate, zinc alloy

System

- Processor Dual-Core Xtensa®, 32 bit ,400 MIPS
- Networking interface 10/100 MbE port
- Power method PoE
- Supported voltage range 44—57V DC
- Max. power consumption 3.5W
- ESD/EMP protection Air: ± 16kV, contact: ± 8kV
- LED R/G/B/W
- Button Factory reset
- Operating temperature 0 to 40° C (32 to 104° F)
- Operating humidity 10 to 90% noncondensing
- Certifications CE, FCC, IC

Audio

- Speaker Yes
- Buzzer Yes

Software

- Web application UniFi Protect
- Mobile app UniFi Protect iOS™ and Android™

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

