

Item no.: UACC-UF-WDM-XGS

UACC-UF-WDM-XGS - UISP Fiber Coexistence WDM Filter

from **269,99 EUR**

Item no.: UACC-UF-WDM-XGS

shipping weight: 2.00 kg

Manufacturer: Ubiquiti

Product Description

Wavelength Division Multiplexing module that combines XGS/XG-PON and GPON services into a single fibre distribution system.

- 24x connectors
- 1U rack mount

Mechanical

- Dimensions: 442 x 120 x 43.7 mm (17.4 x 4.7 x 1.7")
- Weight: 1.8 kg (3.97 lb)
- Enclosure material: Metal
- Connector type: 8x COM (SC/UPC), 8x GPON (SC/UPC), 8x XGS/XG-PON (SC/UPC)

Hardware

- GPON - COM port: Wavelength range: 1290-1330 nm, 1480-1500 nm; Max. insertion loss: 1 dB; Min. isolation: 25 dB
- XGS-PON - COM port: Wavelength range: 1260-1280 nm, 1575-1580 nm; Max. insertion loss: 1 dB; Min. isolation: 25 dB
- Min. return loss: 50 dB
- Max. polarization dependent loss: 0.1 dB
- Fiber type: ITU-T G.657.A1 Single Model Fiber

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

