

Item no.: U-POE++

U-POE++ - UniFi PoE++ Adapter, up to 60 W

from **27,86 EUR**

Item no.: U-POE++
shipping weight: 0.20 kg
Manufacturer: Ubiquiti



Product Description

An adapter that can power UniFi PoE++ devices with wireless mesh applications, or offload PoE switch power dependencies.

- Delivers up to 60 W of PoE++
- Even more power for UA Hub, G4 PTZ, and other PoE++ devices
- Surge, peak pulse, and overcurrent protection
- Contains RJ45 data input, AC cable with earth ground, and PoE++ output
- LED indicator for status monitoring

- Model: U-PoE++
- Dimensions: 106 x 63 x 34 mm (4.2 x 2.5 x 1.3")
- Weight: 210 g (7.4 oz)
- Output voltage: 48 V DC @ 1.25 A
- LAN activity indicator: No
- Gigabit LAN port: Yes
- Remote reset capability: No
- Reset button: No
- Rated voltage: 100-240 V AC @ 50/60 Hz
- Input current: 1.3 A @ 120 V AC; 0.75 A @ 230 V AC
- Inrush current: <100 A peak @ 120 V AC; <200 A peak @ 230 V AC
- Efficiency: 85+%
- Output ripple: 1% max.
- Switching frequency: 65 kHz
- Line regulation: ? 1%
- Load regulation: ? 3%
- 2-pair powering: No
- 4-pair powering: Pins 1, 2, 4, 5 (+) and 3, 6, 7, 8 (-)
- AC connector: IEC-320 C6
- Data in/PoE: RJ45 shielded socket
- Surge protection: Difference and common mode
- Clamping protection: 11 V data, 60 V power
- Max. surge discharge: 1500 A (8/20 ?s) power
- Peak pulse current: 36 A (10/1000 ?s) data
- Shunt capacitance: <5 pF data
- Response time: <1 ns
- Power method: Universal AC input, 100-240 V AC, 50/60 Hz, (48 V @ 1.25 A)
- Power supply: AC/DC
- Supported voltage range: 100-240 V AC
- Max. PoE+ wattage per port by PSE: 60 W
- Operating temperature: 0°C to 40°C (32°F to 104°F)
- Storage temperature: -30°C to 70°C (-22°F to 158°F)
- Operating humidity: 10 to 95% non-condensing
- Certifications: CE, FCC, IC, UL, UKCA, KC, CCC, KC, RoHS

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

