

Item no.: 374180

## UVC-G4 DOORBELL PRO POE KIT-WHITE - UVC-G4 Doorbell Professional PoE Kit, white

from **399,69 EUR**

Item no.: 374180  
shipping weight: 0.60 kg  
Manufacturer: Ubiquiti

### Product Description

Your high-quality UniFi doorbell with integrated PoE and supplied PoE chime for plug-and-play installation.

Specification UVC-G4 Doorbell Pro PoE Dimensions- Device: 160.6 x 51.7 x 35.1 mm (6.3 x 2 x 1.4")- Wall mount: 159.3 x 50.3 x 17.5 mm (6.3 x 1.9 x 0.7")- Wedge: 161.1 x 52.1 x 25.7 mm (6.3 x 2.1 x 1")- Wall Mount: 161.1 x 52.1 x 25.75 mm (6.3 x 2.1 x 1") Weight- Device: 264 g (9.3 oz)- Wall Mount: 56 g (2 oz)- Wedge: 33 g (1.2 oz)- Wall Mount: 53 g (1.9 oz) Housing materials- Aluminium alloy, polycarbonate- Mounting materials Wall bracket: Aluminium alloy- Wedge: Polycarbonate- Wall bracket: Polycarbonate Weather resistance- IPX4 Colour- Black- White Optics- Sensor main camera: 5MP CMOS sensor- Housing camera: 8MP CMOS sensor- Lens fixed focal length- Viewing angle main camera (LDC On): H: 138°, V: 114°, D: 155°- Main camera (LDC Off): H: 160°, V: 117°, D: 160°- Packet camera: H: 97.5°, V: 79.4°, D: 118.2°- Night mode Built-in IR LED illumination and IR cut filter Video- Video compression H.264- Resolution main camera: 2MP 1600 x 1200 (4:3)- Packet camera: 2MP 1600 x 1200 (4:3)- Max. Frame rate 30 FPS System- Processor Quad-Core Arm® Cortex®-A53 based chip- Network interface GbE RJ45 connector- Power supply method PoE- Supported voltage range 37-57V DC- Max. Power consumption 7W- LED link/activity- Buttons (1) bell button, (1) factory reset- Operating temperature -30 to 40° C (-22 to 104° F)- Operating humidity 0 to 90% non-condensing- Certifications CE, FCC, IC Audio- Microphone Yes (can be disabled)- Speaker Yes- Software- UniFi OS Application UniFi Protect- Mobile Application UniFi Protect iOS™ and Android™ Specification UP-Chime PoE Dimensions- Device: Ø62 x 54 mm (Ø2.5 x 2.1")- Wall Mount: Ø89 x 63.1 mm (Ø3.5 x 2.5")- On-Wall Mount: Ø62 x 20.2 mm (Ø2.5 x 0.8")- Weight Device: 158 g (5.6 oz)- Flush-mounted bracket: 91 g (3.2 oz)- Surface mount: 28 g (1 oz) Housing materials- Aluminium alloy, polycarbonate- Mounting materials polycarbonate, zinc alloy System- Dual-core Xtensa® processor, 32 bit, 400 MIPS- Network interface 10/100 MbE connection- Power supply method PoE- Supported voltage range 44-57V DC- Max. Power consumption 3.5 W- ESD/EMP protection air: ± 16kV, contact: ± 8kV- LED R/G/B/W- Factory reset button- Operating temperature 0 to 40° C (32 to 104° F)- Operating humidity 10 to 90% non-condensing- Certifications CE, FCC, IC Audio- Speaker Yes- Buzzer Yes Software- Web application UniFi Protect- Mobile app UniFi Protect iOS™ and Android™

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

