

Item no.: USW-PRO-MAX-24-POE

## USW-PRO-MAX-24-POE-EU - USW-Pro-Max-24-PoE, Pro Max 24 PoE

from **789,62 EUR**

Item no.: USW-PRO-MAX-24-POE

shipping weight: 5.70 kg

Manufacturer: Ubiquiti



### Product Description

A 24-port, Layer 3 Etherlighting™ switch capable of high-power PoE++ output.

Mechanical- Dimensions: 442.4 x 325 x 43.7 mm (17.4 x 12.8 x 1.7")- Weight: Without mounting brackets: 5.1 kg (11.3 lb); With mounting brackets: 5.2 kg (11.5 lb)- Enclosure material: SGCC steelHardware- Management interface: Ethernet In-Band- Networking interface: (16) GbE RJ45 ports; (8) 1/2.5 GbE RJ45 ports; (2) 10G SFP+ ports- PoE interface: (8) PoE/PoE+ (Pins 1, 2+; 3, 6-); (16) 60W PoE++ (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)- Total non-blocking throughput: 56 Gbps- Switching capacity: 112 Gbps- Power method: Universal input, 100—240V AC, 50/60 Hz; - USP RPS DC input- Power supply: AC/DC, internal, 450W- Supported voltage range: 100—240V AC- Max. power consumption: 50W (Excluding PoE output)- Total available PoE: 400W- Max. PoE wattage per port by PS: PoE: 15.4W; - PoE+: 30W; - PoE++: 60W- Voltage range PoE mode: PoE: 44—57V; - PoE+: 50—57V- LCM display: (1) 1.3" touchscreen- Button: Factory reset- Operating temperature: -5 to 40° C (23 to 104° F)- Operating humidity: 10 to 90% noncondensing- Certifications: CE, FCC, IC Etherlighting™- Ethernet: Locating; Speed/link; Native VLAN/network- SFP+: Locating; Speed/link; Native VLAN/networkLEDs- System: Status- RPS: Status

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

