

Item no.: USW-PRO-MAX-48-POE

USW-PRO-MAX-48-POE-EU - USW-Pro-Max-48-PoE, Pro Max 48 PoE

from **1.347,87 EUR**

Item no.: USW-PRO-MAX-48-POE

shipping weight: 6.70 kg

Manufacturer: Ubiquiti



Product Description

A Layer 3 Etherlighting™ switch with 48 ports and PoE++ output with high performance.

Mechanical- Dimensions: 442.4 x 399.6 x 43.7 mm (17.4 x 15.7 x 1.7")- Weight: Without mounting brackets: 6.2 kg (13.7 lb); With mounting brackets: 6.3 kg (13.9 lb)- Housing material: SGCC steelHardware- Management interface: Ethernet In-Band- Network interface: (32) GbE RJ45 ports; (16) 1/2.5 GbE RJ45 ports; (4) 10G SFP+ ports- PoE interface: (8) PoE/PoE+ (Pins 1, 2+; 3, 6-); (16) 60W PoE++ (Pair A 1, 2+; 3, 6-) (Pair B 4, 5+; 7, 8-)- Total non-blocking throughput: 112 Gbps- Switching capacity: 224 Gbps- Power supply: Universal input, 100-240V AC, 50/60 Hz; - USP RPS DC input- Power supply: AC/DC, internal, 820 W- Supported voltage range: 100-240V AC- Maximum power consumption: 100 W (without PoE output)- Total available PoE: 720 W- Max. PoE power per port according to PS: PoE: 15.4 W; - PoE+: 30 W; - PoE++: 60 W- Voltage range PoE mode: PoE: 44-57V; - PoE+: 50-57V- LCM display: (1) 1.3" touchscreen- Button: factory reset- Operating temperature: -5 to 40° C (23 to 104° F)- Operating humidity: 10 to 90% non-condensing- Certifications: CE, FCC, IC Etherlighting™- Ethernet: Localisation; Speed/Link; Native VLAN/Network- SFP+: Localisation; Speed/Link; Native VLAN/NetworkLEDs- System: Status- RPS: Status

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

