

Item no.: USW-ULTRA

USW-ULTRA - compact Layer 2 GbE PoE switch with 8 ports and versatile mounting bracket

from **100,70 EUR**

Item no.: USW-ULTRA
shipping weight: 0.70 kg
Manufacturer: Ubiquiti



Product Description

A compact Layer 2 GbE PoE switch with 8 ports and versatile mounting options. Mechanical- Dimensions: 203 x 76 x 33 mm (8 x 3 x 1.3")- Weight device: 320 g (11.3 oz)- Wall mount: 45 g (1.6 oz)- Housing material polycarbonate Hardware- Management interface: Ethernet In-Band- Network interface: (8) GbE RJ45 ports- PoE interface: (7) PoE/PoE+ (pins 1, 2+; 3, 6-)- Total non-blocking throughput: 8 Gbps- Switching capacity: 16 Gbps- Power supply: (1) 54V, 3.9A power supply (not included) / (1) 54V, 1.1A power supply (not included) PoE++ (pins 1, 2+; 3, 6- and 4, 5+; 7, 8-)- Power supply: 54V, external, 1.1A/60W- Supported voltage range: 44-57V DC- Maximum power consumption: 9W with PoE input (without PoE output) 8W with AC adapter input (without PoE output)- Total available PoE input PoE++: 42W PoE+ input: 16W / 60W PoE adapter input: 42 W 60 W AC adapter input: 52W 210W AC adapter input: 202W*- Max. PoE+ wattage per port through PSE: 30W- Factory button: Reset Operating temperature: PoE++ input: -30 to 60° C (-22 to 140° F) 60W AC adapter input: -20 to 45° C (-4 to 113° F) 210W power supply input: -20 to 60° C (-4 to 140° F)- Operating humidity: 10 to 90% non-condensing- Certifications: CE, FCC, ICLEDS- System: Status- Ethernet: PoE / Link/Activity Application Requirements- UniFi Network Version 8.0.28 and higher* Operating Temperature: 45° C (113° F). Reduced to 161W (230V) or 121W (115V) at 60° C (140° F)

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

