

Item no.: UISP-P

UISP-P - Power management system for MicroPoP applications

from **333,13 EUR**

Item no.: UISP-P
shipping weight: 1.80 kg
Manufacturer: Ubiquiti



Product Description

Uninterruptible power system designed for MicroPoP applications.

- Total power supply: 200 W* (27 V DC)/redundant power supply: 100 W
- 115 Wh Li-ion backup battery
- 1x Power TransPort output
- 1x DC battery port for an external 24 V lead-acid battery (not included)
- Wall-mountable (kit included)
- Compatible with UISP Console, UISP Router (installed with UISP Box), UISP Router Pro, UISP Switch (installed with UISP Box), UISP Switch Pro

*With 2x PSUs installed (sold separately).

Mechanical

- Dimensions: 289 x 280 x 52 mm (11.38 x 11.02 x 2.05")
- Weight: 1.4 kg (3.1 lb)
- Enclosure materials: Polycarbonate, acrylonitrile butadiene styrene

Hardware

- Networking interface: 1x 10/100 MbE RJ45 LAN port
- Management interface: Ethernet In-band, Bluetooth
- Power TransPort output: 27 V DC, 100 W (with 1 power adapter); 27 V DC, 200 W (with 2 power adapters)
- Power method: 2x 27 V DC, 4.4 A power adapters (120 W Power TransPort adapter not included)
- Backup power: 1x 25.2 V DC, 7.93 A rechargeable Li-ion battery pack (included); 1x 24 V DC, 8.33 A lead acid battery input* (battery not included)
- Max. power consumption: 3 W (excludes Power TransPort output and battery charger)
- ESD/EMP protection: Air: ± 15 kV, contact: ± 8 kV
- Operating temperature: -5°C to 40°C (23°F to 104°F)
- Operating humidity: 5 to 95% non-condensing
- Certifications: CE, FCC, IC

LEDs

- System: Status
- RJ45 data port: Link/activity
- Power TransPort: On/Off

Compatibility

- Supported models: UISP Console, UISP Router (installed with UISP Box), UISP Router Pro; UISP Switch (installed with UISP Box); UISP Switch Pro

Software

- Management application: UISP: Version 1.4.5 and later

*Connect to a lead-acid battery only. Using another battery type could be hazardous.

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

