

Item no.: SC-2404-1010-5447

UVC-G3-FLEX - UniFi Video Camera G3 Flex, Full HD, IR, PoE

67,40 EUR

Item no.: SC-2404-1010-5447
 shipping weight: 0.20 kg
 Manufacturer: Ubiquiti



Product Description

Ubiquiti UVC-G3-FLEX - UniFi Video Camera G3 Flex, Full HD, IR, PoE

The UniFi(R) Video Cameras G3 represent the next generation of cameras designed for use in the UniFi Video surveillance management system. These cameras offer 1080p Full HD resolution for day or night use and are integrated with the UniFi Video software for powerful and flexible, integrated IP video management.

The cameras are easy to operate and manage using the UniFi Video(R) software, which is pre-installed on the optional UniFi Application Server and the UniFi NVR appliance, or can be downloaded free of charge.

The UniFi Video Camera G3 Flex features a wideangle lens and 1080p video performance for expanded surveillance coverage. Mounting options include desktop, wall or pole mount for both indoor and outdoor installations. The infrared LEDs and automatic IR cut filter provide highquality day and night monitoring. The G3 Flex also provides an adjustable lens and swivel base for vertical and horizontal viewing angle adjustments.

- 1080p full HD, 25 FPS
- EFL 3.4 mm, /1.2
- Wide-angle lens
- 802.3af PoE
- Built-in microphone
- Desktop, wall or pole mount
- Adjustable lens and swivel base for vertical and horizontal viewing angle adjustments

- Dimensions: 107.5 x 48 mm (4.23 x 1.89")
- Weight: 170 g (6 oz)
- Networking interface: (1) 10/100 Ethernet port
- Sensor: 1/3" 2-Megapixel HDR sensor
- Lens: EFL 3.4 mm, f/1.2
- Night mode: IR LEDs with mechanical IR filter
- Microphone: Yes
- Button: Factory reset button
- Power method: 802.3af PoE
- Maximum power consumption: 4 W
- Mounting: Table/wall/pole
- Operating temperature: -20°C to 50°C (-4°F to 122°F)
- Operating humidity: 20 - 90% non-condensing
- Video compression: H.264
- Resolution: 1080p full HD (1920x1080)
- Maximum frame rate: 25 FPS
- Image settings: Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz
- Viewing angle:
 - Lens correction off: 87.4° (H), 47° (V), 104° (D)
 - Lens correction on: 80° (H), 46° (V), 92° (D)
- Supported UniFi Video version: UniFi Video 3.9.2 (or newer)
- UniFi Video system requirements: 64-bit Microsoft Windows 10/8/7, Ubuntu 14.04 or 16.04, or Debian 7.0 System with an Intel or compatible 1.86 GHz (or above) processor and a minimum of 4 GB RAM
- Mobile apps: UniFi Video, iOS and Android

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

