

Item no.: BR700ELCD

## BR700ELCD - Line-Interactive UPS 700 VA / 390 W

from **139,40 EUR**

Item no.: BR700ELCD  
shipping weight: 5.90 kg  
Manufacturer: CyberPower



### Product Description

CyberPower BR700ELCD - Line-Interactive UPS 700 VA / 390 W The BRICs LCD Series UPS offers home and small office users a clean and stable battery backup while the featured RJ11/RJ45 port ensures phone, fax, and modem lines are protected from surges. The Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, which allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The multifunctional LCD readout provides immediate access to precise information of critical power/battery conditions. For convenient mounting, these units can be installed in either a horizontal or wall-mounted placement to make the most of your space. The included PowerPanel(R) Personal Edition management software showcases the feature-rich abilities such as input/output power voltage readings, self-diagnostics, and approximate battery backup time. With the Energy-Saving Technology, the BRICs LCD Series UPS can save up to 75% of electricity, therefore save your electricity expenses. Features & Benefits

- GreenPower UPS(TM) Technology : Energy-Saving UPS
- Automatic Voltage Regulation (AVR)
- EMI, RFI, Surge and Spike Protection
- Phone/Fax/Modem/DSL/Network Protection
- Auto-Restart/Auto-Charge
- LCD Status Monitor
- USB Connectivity Port
- User-Replaceable Batteries
- Horizontal / Wall-mounted Use
- Cable Collector Included
- PowerPanel(R) Personal Edition Software

#### General

- UPS Topology: Line-interactive
- Energy Saving: Yes

#### Input

- Voltage: 220/230/240 Vac
- Input Voltage Range: 165 - 290 V ac
- Rated Input current: 3.18 A
- Plug Type: Schuko
- Input Frequency Range: 45 ~ 65 Hz

#### Output

- VA: 700
- Watts: 420
- On Battery Waveform: Simulated Sine Wave
- On Battery Voltage: 220-240 V ac
- Automatic Voltage Regulation (AVR): Single Boost / Single Buck
- On Battery Frequency: 50/60 Hz +/- 1 %
- Outlets - Total: 8
- Outlet Type: Schuko
- Outlets - Battery & Surge Protected: 4
- Outlets - Surge-Only Protected: 4
- USB Charging Ports: Yes
- Transfer Time: 4 ms

#### Battery

- Runtime at 60 W (min): 47
- Runtime at 90 W (min): 28
- Battery Type: Sealed Lead Acid
- Battery Quantity: 1
- User Replaceable: Yes
- Hot-Swappable: Yes
- Typical Recharge Time: 8 Hours
- Replacement Battery Pack: RBP0083
- Replacement Battery Pack Quantity: 1

#### Surge Protection and Filtering

- Surge Suppression: 125 Joules (L-N)
- Phone / Network Protection RJ11/RJ45: 1-In, 1-Out (Combo)

#### Management & Communications

- LCD Control Panel: Yes
- HID Compliant USB Port: Yes
- LED Indicators: Yes
- Audible Alarms: On Battery, Low Battery, Overload, Fault
- Software: PowerPanel(R) Personal Edition

#### Physical

- Form Factor: Brick
- Dimensions (W x H x D) (mm): 166 x 118 x 288
- Weight (kg): 5.3

#### Environmental

- Operating Temperature: +32 °F to 104 °F / 0 °C to 40 °C
- Operating Humidity: 0 % - 90 % non-condensing
- Operating Elevation: 0 - 10000 feet (0-3000meters)
- Storage Temperature: -4 °F to 122 °F / -20 °C to 50 °C
- Storage Relative Humidity: 0 % - 90 %
- Online Thermal Dissipation: 71 BTU/hr

## Specifications

---

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

