

Item no.: 384498

## A245SUS - QuSpot for TRB245/255 (incl. Band 71)

from **83,07 EUR**

Item no.: 384498  
 shipping weight: 1.50 kg  
 Manufacturer: QuWireless



### Product Description

INTEGRATED MULTI-BAND LTE OMNI ANTENNA + GPS ANTENNA + POE SPLITTER + PLACE TO INSTALL TELTONIKA TRB245/TRB255 (ALL-IN-ONE) QuSpot omni LTE antenna for Teltonika TRB245 or TRB255 gateway is a perfect outdoor device for mobile and fixed installations like industrial, hotspots, yachts, boats, campers, RV etc. The LTE/5G antenna supports band 71. It has embedded also GPS antenna. If you use TRB245/TRB255 with QuSpot antenna, you get an integrated complete solution with embedded gateway and multi band antennas in one enclosure. The set contains a PoE splitter, allowing to provide both data and power via one Ethernet cable and keep Gigabit transfer speeds. LTE ANTENNA SPECIFICATION FREQUENCY- 617 - 960 MHz- 1.7 - 2.2 GHz- 2.3 - 2.7 GHz- 3.3 - 3.8 GHz GAIN- 617 - 960 MHz : 3 dBi- 1.7 - 2.2 GHz : 3.5 dBi- 2.3 - 2.7 GHz : 3.5 dBi- 3.3 - 3.8 GHz : 4dBi SUPPORTED LTE/5G BANDS- 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 23, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 48, 49, 52, 53, 59, 62, 65, 66, 67, 68, 69, 71, 85, n78, n80, n81, n82, n83, n84, n86, n89, n90, n95 VSWR- <1.80, max <2.00 BEAMWIDTH- 360°/35° ±5° POLARIZATION- Vertical IMPEDANCE- 50 Ω MECHANICAL SPECIFICATION MATERIALS- ABS, aluminum, PTFE, Fiberglass CONNECTOR TYPE- RJ45 INGRESS PROTECTION- IP67 DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch WEIGHT- 1.5 kg- 3.31 lbs OPERATING TEMPERATURE- From -40°C to 75°C- From -40°F to 167°F MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

### Specifications

Scan this QR code to  
 view the product

All details, up-to-date  
 prices and availability

