

Item no.: 384499

A240SUS - QuSpot for RUT241RUT240200230, ver US (Band 71)

from **89,11 EUR**

Item no.: 384499
shipping weight: 1.50 kg
Manufacturer: QuWireless



Product Description

Integrated multi-band LTE omni antenna ver. US + WiFi omni antenna + place to install Teltonika RUT241, RUT240 or 230 (All-in-one) QuSpot omnidirectional LTE antenna ver. US for Teltonika RUT260, RUT241, RUT240, RUT230 or RUT200 routers is a perfect outdoor device for mobile and fixed installations e.g. CCTV, hotspots, industrial areas, campervans, ships etc.. In addition to having omnidirectional, multi-band LTE antennas, it has also embedded omnidirectional Wi-Fi antenna. If you use RUT2xx with QuSpot antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure. LTE ANTENNA SPECIFICATION FREQUENCY- 617 - 960 MHz- 1.7 - 2.2 GHz- 2.3 - 2.7 GHz- 3.3 - 3.8 GHz GAIN- 617 - 960 MHz : 3 dBi- 1.7 - 2.2 GHz : 3.5 dBi- 2.3 - 2.7 GHz : 3.5 dBi- 3.3 - 3.8 GHz : 4dBi SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106 VSWR- <1.80, max <2.00 BEAMWIDTH- 360°/35° ±5° POLARIZATION- Vertical IMPEDANCE- 50 Ω MECHANICAL SPECIFICATION MATERIALS- ABS, aluminum, PTFE CONNECTOR TYPE- RJ45 INGRESS PROTECTION- IP67 DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch WEIGHT- 1.5 kg- 3.31 lbs OPERATING TEMPERATURE- From -40°C to 80°C- From -40°F to 176°F MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

