

Item no.: 374533

UISP-S-PLUS - Ubiquiti UISP-S-Plus

from **428,52 EUR**

Item no.: 374533
shipping weight: 2.30 kg
Manufacturer: Ubiquiti



Product Description

2.5 GbE PoE switch for ISP applications. Mechanical- Dimensions: 210.4 x 170.2 x 43.7 mm (8.3 x 6.7 x 1.7")- Weight: 1.75 kg (3.9 lb)- Housing materials: SGCC steel, polycarbonate/acrylonitrile butadiene styrene Hardware- Processor: Dual-core ARM@v8 Cortex@-A55 with 1.4 GHz- Memory: 1 GB DDR4- Onboard flash memory: 256 MB NAND- Network interface: (4) 1/2.5 GbE RJ45 LAN ports, (4) 1/10G SFP+ ports- Management interface: Ethernet in-band; Bluetooth- Total non-blocking throughput: 50 Gbps- Switching capacity: 100 Gbps- Forwarding rate: 74.4 Mpps- Power supply: (1) External AC/DC adapter; (1) Power TransPort DC input 27V DC, 7.04A- Power supply: 27V DC, 7.04A power supply (included)- Supported voltage range: 24-28V DC- Maximum power consumption: 25W (without PoE output.)- ESD/EMP protection: air: ± 15 kV, contact: ± 8 kV- Operating ambient temperature: -10 to 50° C (14 to 122° F)- Operating humidity: 5 to 95% non-condensing- Certifications: CE, FCC, ICPoE- PoE interface: (4) 27V passive PoE: 2-pair (pins 4, 5+/7, 8-) or 4-pair (pins 1, 2, 4, 5+/3, 6, 7, 8-); ports 1 to 4- Total PoE power available: 160W (With included power supply.)- Maximum passive PoE power per port: 2-pair mode: 20W/27V DC; 4-pair mode: 40W/27V DC- Passive PoE voltage range: 27V DCLeds- System: Status- RJ45 data ports: PoE; speed/link/activity- SFP+ data ports link/activity Software- Management application: UISP

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

