

Item no.: 384314

APBM5M - QuMax for Peplink MAX BR1 Mini 5G

from **190,28 EUR**

Item no.: 384314
 shipping weight: 2.80 kg
 Manufacturer: QuWireless



Product Description

INTEGRATED MULTI-BAND LTE & 5G PANEL ANTENNA + PLACE TO INSTALL PEPLINK MAX BR1 MINI 5G (ALL-IN-ONE) QuMax for Peplink MAX BR1 Mini 5G is a high performance directional antenna designed for use in a variety of wireless communication applications. This all-in-one product consists of multi-band 5G antennas integrated in IP67 enclosure. It offers 7.5 dBi gain and wide beamwidth, which makes it suitable for use in both urban and rural environments. Combining QuMax with Peplink MAX BR1 Mini 5G inside the antenna housing gives you complete outdoor solution with multiple use scenarios such as transportation public, energy, mining IoT and more. 5G / LTE ANTENNA SPECIFICATION

FREQUENCY- 0.617 - 0.96 GHz- 1.7 - 2.7 GHz- 3.3 - 4.6 GHz- 4.7 - 6.0 GHz GAIN- 0.617 - 0.96 GHz: 6 dBi- 1.7 - 2.7 GHz: 7 dBi- 3.3 - 4.6 GHz: 7 dBi- 4.7 - 6.0 GHz: 5.5 dBi SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 46, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106 SUPPORTED 5G BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n46, n47, n48, n53, n65, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256 VSWR- <2.00, max <3.00 BEAMWIDTH- 80°/80° ±15° POLARIZATION- X (+45degrees) IMPEDANCE- 50 Ω MECHANICAL SPECIFICATION MATERIALS- ABS, aluminum, PTFE, Fiberglass CONNECTOR TYPE- RJ45 INGRESS PROTECTION- IP67 DIMENSIONS- 486.0 x 292.2 x 175.6 mm- 19.13 x 11.50 x 6.87 inch WEIGHT- 2.8 kg- 6.17 lbs OPERATING TEMPERATURE- From -40°C to 80°C- From -40°F to 176°F MAST DIAMETER- 25-60mm- 0.98-2.36 inch

Specifications

Scan this QR code to view the product
 All details, up-to-date prices and availability

