

Item no.: 384328

AEG5120MO - QuMax Omni with PoE Splitter for Robustel EG5120

from 234,80 EUR

shipping weight: 0.80 kg Manufacturer: QuWireless

Product Description

INTEGRATED MULTI-BAND 5G OMNI ANTENNA + WIFI OMNI ANTENNA + BLUETOOTH ANTENA + GPS ANTENNA + PLACE TO INSTALL ROBUSTEL EG5120 INTEGRATED MULTI-BAND 5G OMNI ANTENNA + WIFI OMNI ANTENNA + BLUETOOTH ANTENA + GPS ANTENNA + PLACE TO INSTALL ROBUSTEL EG5120 (ALL-IN-ONE)QuMax Omni all-in-one antenna for Robustel EG5120 router is a perfect outdoor device for mobile and fixed installations like industrial, public, CCTV, hotspots, yachts, boats, campers, RV etc. It has embedded om 4*5G, 2*Wi-Fi, Bluetooth and GPS antenna. If you use EG5120 with QuMax Omni antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure. The set contains a PoE splitter, allowing to provide both data and power via one Ethernet cable and keep Gigabit transfer speeds.5G / LTE SPECIFICATIONFREQUENCY- 617 - 960 MHz- 1.7 - 2.7 GHz- 3.3 - 4.7 GHz- 5.2 - 6.0 GHzGAIN- 617 - 960 MHz: 3 dBi- 1.7 - 2.7 GHz: 4 dBi- 3.3 - 4.7 GHz: 4.5 dBi- 5.2 - 6.0: 2.5dBiSUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106SUPPORTED GB BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n47, n48, n53, n66, n66, n67, n71, n77, n78, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n88, n100, n101, n256VSWR- <1.80, max <2.00BEAMWIDTH- 360°/35° +/- 5°POLARIZATION- VerticalIMPEDANCE- 50 ?WI-FI SPECIFICATIONFREQUENCY- 2.4 - 2.5 GHz- 5.0 - 6.0 GHzGAIN- 2.4 - 2.5 GHz: 6 dBi- 4.7 - 6 GHz: 7 dBiVSWR- <1.70, max <2.00BEAMWIDTH- 360°/25° +/- 5°POLARIZATION- PerfcoNNECTOR TYPE- RJ45DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inchWEIGHT- 1.8 kg- 3.97 lbsOPERATING TEMPERATURE- From -40°C to 75°C- From -40°F to 167°F TEMPERATURE- From -40°C to 75°C- From -40°F to 167°F

Specifications

Scan this QR code to view the product

All details, up-to-date prices and availability

