

Item no.: 384312

## APBM3M - QuMax for Peplink MAX BR1 Mini (HW3)

from **174,10 EUR**

Item no.: 384312  
 shipping weight: 2.80 kg  
 Manufacturer: QuWireless



### Product Description

**INTEGRATED MULTI-BAND 5G DIRECTIONAL ANTENNA + WI-FI OMNI ANTENNA + GPS ANTENNA + PLACE TO INSTALL PEPLINK MAX BR1 MINI (HW3) & M2M (ALL-IN-ONE)** QuMax antenna for Peplink MAX BR1 Mini (HW3) & M2M router is a perfect outdoor device for improving the signal in rural/suburban and locations where the mobile signal is weak. It has embedded directional 5G, omni Wi-Fi and GPS antenna. If you use MAX BR1 Mini (HW3) or M2M with QuMax antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure.

**5G / LTE ANTENNA SPECIFICATION**  
 FREQUENCY- 617 - 960 MHz- 1.7 - 2.7 GHz- 3.3 - 4.6 GHz- 4.7 - 6.0 GHz  
 GAIN- 617 - 960 MHz : 6 dBi- 1.7 - 2.7 GHz : 7 dBi- 3.3 - 4.6 GHz : 7 dBi- 4.7 - 6.0 GHz : 5.5dBi  
 SUPPORTED LTE BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 22, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 46, 47, 48, 49, 52, 53, 65, 66, 67, 68, 69, 71, 85, 103, 106  
 SUPPORTED 5G BANDS- n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n46, n47, n48, n53, n65, n66, n67, n71, n77, n78, n79, n80, n81, n82, n83, n84, n85, n86, n89, n90, n95, n97, n98, n100, n101, n256  
 VSWR- <2.00, max <3.00  
 BEAMWIDTH- 80°/80° ±15°  
 POLARIZATION- X (+45degrees)  
 IMPEDANCE- 50 Ω

**WI-FI ANTENNA SPECIFICATION**  
 FREQUENCY- 2.4 - 2.5 GHz- 4.7 - 6.0 GHz  
 GAIN- 2.4 - 2.5 GHz : 6 dBi- 4.7 - 6.0 GHz : 7 dBi  
 VSWR- < 1.70, max < 2.00  
 BEAMWIDTH- 360°/25°  
 POLARIZATION- Vertical  
 IMPEDANCE- 50 Ω

**MECHANICAL SPECIFICATION**  
 MATERIALS- ABS, aluminum, PTFE, fiberglass  
 CONNECTOR TYPE- RJ45  
 INGRESS PROTECTION- IP67  
 DIMENSIONS- 26.9 x 26.95 x 17.7 cm- 10.6 x 10.6 x 7 inch  
 WEIGHT- 2.8 kg- 6.17 lbs  
 OPERATING TEMPERATURE- From -40°C to 80°C- From -40°F to 176°F  
 MAST DIAMETER- 25-60mm- 0.98-2.36 inch

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

