

Item no.: AF-5G23-S45

## AF-5G23-S45 - airFiber Antenna, 5.1 - 5.9 GHz, 23 dBi

from **95,06 EUR**

Item no.: AF-5G23-S45  
 shipping weight: 5.30 kg  
 Manufacturer: Ubiquiti



### Product Description

airFiber Antenna AF-5G23-S45 Pair an airFiber X antenna with an airFiber X radio to create the endpoint of a high-performance, Point-to-Point (PtP) bridge or network backhaul (airFiber X radio sold separately). Powerful Performance The airFiber X antenna delivers 2x2, dual-polarity performance. On the right is one example of how the airFiber X antenna with an airFiber X radio can be deployed in a backhaul link to deliver bandwidth from an ISP network out to a neighborhood tower. From there, an airMAX Sector antenna with a Rocket(TM) radio delivers bandwidth to the ISPs customers. Carrier-Class Construction Incorporating a dish reflector design for excellent beam directivity, the airFiber X antennas feature robust mechanical design using industrial-strength hardware for outdoor application use. Plug and Play Integration airFiber X antennas and airFiber X radios have been designed to seamlessly work together. Every airFiber X antenna has a built-in airFiber X radio mount, so installation requires no special tools. Snap the airFiber X radio securely into place and mount the antenna; you then have the optimal combination of airFiber X antenna and airFiber X radio for your PtP application. Hardware Overview Innovative Mechanical Design

- Secure Pole-Mounting: The hardware is designed to securely mount and maintain the position of the dish during harsh outdoor conditions.
- Convenient Installation: The bubble level allows for easy alignment.
- Precision Elevation Adjustment of the AF-5G30-S45: Use this new feature to quickly fine-tune and adjust the elevation.

#### Weatherproof Design

- Protective Shroud: The shroud protects the cables and connectors from nature's elements.
- Mounting Hardware of the AF-5G30-S45: Made of galvanized steel that is powder-coated for superior corrosion resistance.
- Fasteners of the AF-5G30-S45: GEOMET-coated for improved corrosion resistance when compared with

- Model: AF-5G23-S45
- Dimensions: 378 x 378 x 290 mm (14.88 x 14.88 x 11.42")
- Weight: 3.4 kg (7.5 lb)
- Frequency Range: 5.1 - 5.9 GHz
- Gain: 23 dBi
- + 45° Beamwidth: 10° (3 dB)
- - 45° Beamwidth: 10° (3 dB)
- F/B Ratio: 30 dB
- Max. VSWR: 1.5:1
- Wind Loading: 190 N (at) 200 km/h (43 lbf (at) 125 mph)
- Wind Survivability: 200 km/h (125 mph)
- Polarization: Dual-Linear
- Cross-pol Isolation: 35 dB Min.
- ETSI Specification: EN 302 326 DN2
- Mounting: Universal Pole Mount, airFiber X Radio Bracket, and Weatherproof RF Connectors Included

### Specifications

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability



