

Item no.: 384522

## SS17HV.90.4RT - QuSector S17HV-90-5 4x RPTNC



from **167,35 EUR**

Item no.: 384522  
shipping weight: 1.80 kg  
Manufacturer: QuWireless

### Product Description

QuSector 17HV-90-4 offers a 90 degrees, 17dBi gain signal with four dual-band connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector 17HV-90-4 is a concurrent, dual-band, H&V polarity, MIMO 4x4 panel antenna. It simultaneously operates at 2.4GHz with 14dBi gain and 5GHz with 17dBi gain. Due to its high gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in three configurations: with 4\*70cm (28inch) cables terminated with Nm, RPSMA or RPTNC connectors. QuSector 17HV-90-4 was designed to be a perfect match for your access point. Wi-Fi SPECIFICATION FREQUENCY- 2.4 - 2.5GHz- 5.1 - 5.9GHz GAIN- 14 dBi- 17 dBi VSWR- < 1.80 BEAMWIDTH- 90°/16°- 90°/8° POLARIZATION- Horizontal- Vertical IMPEDANCE- 50 Ω SEPARATION BETWEEN CONNECTORS- > 30dB FRONT-TO-BACK- > 23dB- > 20dB MAX INPUT POWER- 50W DC GROUND- Yes MECHANICAL SPECIFICATION MATERIAL- ABS CONNECTOR- 4x RPTNC OUTER DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch WEIGHT- 1.8 kg OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F MOUNTING KIT DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch REGULATION RANGE- +/- 30° MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts MOUNTING PLACE- Wall or ceiling or mast

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

