

Item no.: 384445

## S14HV.90.2NM - QuSector 14HV-90-2 Wi-Fi 6E 2x Nm

from **167,35 EUR**

Item no.: 384445  
 shipping weight: 1.80 kg  
 Manufacturer: QuWireless



### Product Description

QuSector 14HV-90-2 offers a 90 degrees, 14dBi gain signal with two RP-SMA 2.4GHz and 5GHz+7GHz connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector 14HV-90-2 is a dual band, concurrent, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz and 5GHz+7GHz. It is a futureproof solution with Wi-Fi 6E and Wi-Fi 7 support. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in three configurations: with 2\*70cm (28inch) cables terminated with Nm, RPSMA and RPTNC connectors. QuSector 14HV-390-2 was designed to be a perfect match for your access point. Wi-Fi

SPECIFICATION FREQUENCY- 2.4 - 2.5 GHz- 5.0 - 7.125 GHz GAIN- 12 dBi- 14 dBi SWR- < 2.00 BEAMWIDTH- 90°/30°- 90°/16° POLARIZATION- Horizontal- Vertical IMPEDANCE- 50 Ω SEPARATION BETWEEN CONNECTORS- >30 dB FRONT-TO-BACK- > 20dB- >25dB MAX INPUT POWER- 50W DC GROUND- Yes MECHANICAL SPECIFICATION MATERIAL- ABS CONNECTOR- 2x N MOUNTING DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch WEIGHT- 1.8 kg OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F MOUNTING KIT DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch REGULATION RANGE- +/- 30° MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts MOUNTING PLACE- Wall or ceiling or mast

### Specifications

Scan this QR code to  
 view the product  
 All details, up-to-date  
 prices and availability

