

Item no.: 384421

## S14HV.90.3RS - QuSector 14HV-90-3 Wi-Fi 6E 3x RPSMA



from **219,78 EUR**

Item no.: 384421  
shipping weight: 1.80 kg  
Manufacturer: QuWireless

### Product Description

QuSector 14HV-90-3 offers a 90 degrees, 14dBi gain signal with two RP-SMA 2.4GHz connectors. It is a perfect indoor and outdoor device for industrial installations. QuSector 14HV-90-3 is a single band, H&V polarity, MIMO 3x3 panel antenna. Two connectors operate at 2.4GHz with 14dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in following configurations: 3\*70cm (28inch) cables terminated with Nm, RPSMA, RPTNC connectors. QuSector 14HV-90-3 was designed to be a perfect match for your access point. Wi-Fi SPECIFICATION FREQUENCY- 2.4 - 2.5GHz- 5.1 - 5.9GHz GAIN- 12 dBi- 14 dBi VSWR- < 2.00 BEAMWIDTH- 90°/30°- 90°/16° POLARIZATION- Horizontal- Vertical IMPEDANCE- 50 Ω SEPARATION BETWEEN CONNECTORS- >30 dB FRONT-TO-BACK- > 20dB- >25dB MAX INPUT POWER- 50WDC GROUND- Yes MECHANICAL SPECIFICATION MATERIAL- ABS CONNECTOR- 3xRPSMA OUTER DIMENSIONS- 29.2 x 48.6 x 10.6 cm- 11.5 x 19.13 x 4.17 inch WEIGHT- 1.8 kg OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F MOUNTING KIT DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch REGULATION RANGE- +/- 30° MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts MOUNTING PLACE- Wall or ceiling or mast

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

