

Item no.: 384448

S12HV.30.2RT - QuSector 12HV-30-2 2x RPTNC

from **168,08 EUR**

Item no.: 384448
 shipping weight: 1.80 kg
 Manufacturer: QuWireless



Product Description

QuSector 12HV-30-2 offers a 30 degrees, 12dBi gain signal with two 2.4GHz+5GHz connectors. It is a perfect indoor and outdoor device for industrial installations. -End of Life- QuSector 12HV-30-2 is a dual band, concurrent, H&V polarity, MIMO 2x2 panel antenna. Two connectors operate at 2.4GHz+5GHz with 12dBi gain. Due to its medium gain, it can be used on short or medium distances, for example for hotspots in schools, stadiums, offices or public places. High quality injection moulded enclosure allows to implement it alongside with indoor and IP67 outdoor solutions. The antenna comes in the following configurations: with 2*70cm (28inch) cables terminated with Nm, RPSMA, RPTNC connectors. QuSector 12HV-30-2 was designed to be a perfect match for your access point. WE REGRET TO INFORM YOU THAT THE PRODUCT HAS REACHED ITS END OF LIFE (EOL). A NEWER AND BETTER VERSION IS NOW OUT. CHECK IT OUT HERE: QuSector 14HV-30-2 Wi-Fi 6e Wi-Fi SPECIFICATION FREQUENCY- 2.4 - 2.5GHz- 5.1 - 5.9GHz GAIN- 12 dBi VSWR- < 2.00 BEAMWIDTH- 35°/35° POLARIZATION- Horizontal- Vertical IMPEDANCE- 50 Ω SEPARATION BETWEEN CONNECTORS- >25dB FRONT-TO-BACK- > 20dB- > 25dB MAX INPUT POWER- 50W DC GROUND- Yes MECHANICAL SPECIFICATION MATERIAL- ABS CONNECTOR- 2x RPTNC OUTER DIMENSIONS- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch WEIGHT- 1.8 kg OPERATING TEMPERATURE- -40°C to +80°C- -40°F to 176°F MOUNTING KIT DIMENSIONS- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch REGULATION RANGE- +/- 30° MAST DIAMETER RANGE- 25 - 60mm- 0.98-2.36 inch MATERIAL- Polyamide with fiberglass + galvanized steel U-Bolts MOUNTING PLACE- Wall or ceiling or mast

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

