

Item no.: 332901

DECO P9(2-PACK) - Deco P9 - AC1200 + AV1000 Powerline Mesh Wi-Fi System, 2-Pack

from **164,00 EUR**

Item no.: 332901
shipping weight: 1.50 kg
Manufacturer: TP-LINK



Product Description

Deco P9 - AC1200 + AV1000 Whole Home Powerline Mesh Wi-Fi System, 2-Pack

Deco P9 combines dual-band Wi-Fi and powerline to establish a stronger mesh network. Powerline technology uses your homes electrical wiring to create stronger connections between Deco units, reducing the impact of walls and other obstacles on signal and providing even faster network speeds and truly seamless coverage. Dead-Zone Killer

The hybrid whole-home system delivers extended coverage up to 4,000 ft²/370 m² with the help of the combination of dual-band Wi-Fi and powerline. Eliminate weak signal areas with whole-home Wi-Fi and no more searching around for a stable connection. Seamless Roaming with One Wi-Fi Name

TP-Link Mesh means Deco units work together to form one unified network. Your phone or tablet automatically connects to the fastest Deco as you move through your home, creating a truly seamless Wi-Fi experience.

Hardware

- Ports: 2x WAN/LAN Gigabit Ethernet ports, 1x Power port
- Buttons: 1x Reset button on the underside
- Antenna type: 2x internal dual-band antennas per Deco unit
- Dimensions: 7.5 x 3.6 x 3.6 in. (190.5 x 90.7 x 90.7 mm)
- Power input: 100-240 V ~ 50/60 Hz, 0.5 A

Wireless

- Wireless standards: IEEE 802.11 ac/n/a 5 GHz, IEEE 802.11 b/g/n 2.4 GHz
- Frequency: 2.4 GHz and 5 GHz
- Signal rate: 867 Mbps at 5 GHz, 300 Mbps at 2.4 GHz
- Transmit power: FCC:
- Wireless security: WPA-PSK/WPA2-PSK

Software

- Working mode: Router, access point
- WAN type: Dynamic IP/static IP/PPPoE/L2TP/PPTP
- DHCP: Server, client
- Quality of Service: WMM
- Firewall security: SPI firewall
- Protocols: Supports IPv4 and IPv6
- Guest network: 1x 2.4 GHz guest network, 1x 5 GHz guest network
- Features: Parental controls, QoS (Quality of Service), reporting, assisted setup, address reservation, port forwarding, TP-Link DDNS, VLAN, IPv6, LED control
- Management: Local management, remote management

Powerline

- Powerline rate: 1000 Mbps
- Standard: HomePlug AV2
- Range: 300 meters/1000 feet over electrical circuit

Others

- Certification: CE, FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC, RoHS
- Smartphone/tablet requirements: iOS 9.0 or later; Android 4.4 or later
- Environment: Operating temperature: 0°C ~ 40°C (32°F ~ 104°F); Storage temperature: -40°C ~ 70°C (-40°F ~ 158°F); Operating humidity: 10% ~ 90% non-condensing; Storage humidity: 5% ~ 90% non-condensing
- Package contents for Deco P9 (2-pack): 2x Deco P9 units (routers with powerline); 1x RJ45 Ethernet cable; 2x power cords

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

