

Item no.: 332938

TD-W9960V(DE) - VDSL2 modem router, 3 ports

from **69,71 EUR**

Item no.: 332938
shipping weight: 0.80 kg
Manufacturer: TP-LINK



Product Description

TD-W9960v - DSL modem router Enjoy a super fast Connection to the VDSL modem router

The latest VDSL2 technology enables the DSL Internet Box to deliver impressive VDSL broadband speeds of up to 100 Mbit / s, which is almost five times faster than ADSL2 +. The built-in DSL port supports all standard DSL connections * to ensure compatibility with most ISPs such as Telekom, 1 & amp; 1, Vodafone and O2. The DSL Internet Box serves as a DSL modem and WLAN router and combines two devices in one.

* The DSL Internet Box is compatible with VDSL2, ADSL2 +, ADSL2 and ADSL. Intelligent and convenient telephony

Use the DSL Internet Box for all your extended landline calls. Connect up to 6x DECT handsets with a voice signal in HD quality as well as an analog telephone or fax machine and enjoy a complete telephony system at home or in the office.

With the tpPhone app, you can use your smartphone to make landline calls with high fidelity over the Internet without additional DECT cell phones. The intuitive visual user interface makes it easy to view a list of voice messages, review missed calls, and initiate three-way conference calls. Easy to set up and manage

Set up the DSL Internet Box in a few minutes thanks to the intuitive web interface and the powerful tether app. Manage network settings, including parental controls and access control, from any Android or iOS device. Control your home network whenever and wherever you are.

Hardware functions

- Ports: 3x RJ45 LAN ports with 10/100 Mbit / s, 1x RJ45 LAN / WAN port with 10/100 Mbit / s, 1x RJ11 port, 1x TAE port
- Button: WPS, reset, switch on / off, DECT
- External power supply: 12 V / 1 A
- IEEE standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab
- VDSL2 standards: ITU-T G.993.2, up to profile 17a (ISDN); ITU-T G.993.5 (G.vector); ITU-T G.998.4 (G.INP)
- ADSL standards: Full-Rate-ANSI T1.413, Issue 2; ITU-T G.992.1 (G.DMT); ITU-TG.992.2 (G.Lite); ITU-T G.994.1 (G.hs)
- ADSL2 standards: ITU-T G.992.3 (G.DMT.bis)
- ADSL2 + standards: ITU-T G.992.5
- Dimensions: 217.7 x 173.5 x 36.8 mm
- Antenna gain: 2x 5 dBi

WLAN functions

- WLAN standards: IEEE 802.11b / g / n
- WiFi speeds: 300 Mbit / s
- Frequency: 2.4 GHz
- Transmission power:
- WLAN security: 64/128-bit WEP, WPA / WPA2, WPA-PSK / WPA-PSK2 encryption

VoIP functions

- VoIP standards: SIP (RFC3261) / RTP (RFC1889 / 3550), G.711A / u, G.722, G.729AB, G.726
- DECT function: DECT base station compatible with CAT-iq and GAP for up to 6 cordless telephones, supports the paging function

Software features

- Operating modes: VDSL / ADSL modem router, WLAN router
- DHCP: server, client, address reservation, DHCP delay
- Port forwarding: virtual server, port triggering, DMZ, ALG, UPnP
- Dynamic DNS: DynDNS, No-IP, TP-Link, DuckDNS, DtdNS, YDNS, DYNU, FreeDNS, AnyDNS, Selfhost, SPDNS, user-defined
- VPN: OpenVPN, PPTP VPN, IPsec VPN
- Protocols: Supports IPv4 and IPv6
- ATM / PPP protocols: ATM-Forum UNI3.1 / 4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577 / 2225), MER \ IPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC - up to 8 PVCs
- Extended functions: Parental controls, network address translation (NAT), port assignment (grouping), static routing, RIP v1 / v2 (optional), DNS relay, DDNS, IGMP V1 / V2 / V3
- IPsec VPN: Supports up to 10 IPsec VPN tunnels

Other

- Certification: CE, RoHS
- Package content: DSL Internet BOX TD-W9960v, external splitter, RJ11 DSL cable, RJ45 Ethernet cable, power supply unit, quick installation guide
- System requirements: Microsoft Windows 98SE, NT, 2000, XP, Vista (TM) or Windows 7, 8, 8.1, 10, Mac OS, NetWare, UNIX or Linux; Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 or another Java-enabled browser
- Environment: Operating temperature: 0 ° C ~ 40 ° C (32 ° F ~ 104 ° F); Storage temperature: -40 ° C ~ 70 ° C (-40 ° F ~ 158 ° F); Operating humidity: 10% ~ 90% non-condensing; Storage humidity: 5% ~ 90% non-condensing

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

