

Item no.: 356382

## Mobile 600 Mbit/s LTE WLAN router

from **166,91 EUR**

Item no.: 356382  
shipping weight: 0.30 kg  
Manufacturer: TP-LINK



### Product Description

The M7650 supports 4G/LTE (LTE-A Cat.11) and uses Carrier Aggregation for this. This technology combines distant LTE frequencies into a "virtual" frequency band to increase throughput up to 600 Mbps. This allows you to enjoy smooth HD streaming, fast downloads and smooth online gaming.

- Supports LTECAT11 up to 600 Mbps download and 50 Mbps upload
- Simultaneous surfing with up to 32 devices
- Dual-band WLAN with up to 300 Mbps on the 2.4 GHz band or up to 867 Mbps on the 5 GHz band
- 3000mAh battery provides power for up to 15 hours of operation
- Micro SD card slot for up to 32GB of additional storage space
- Easy management thanks to the tpMiFi app
- The display gives you all the important information at a glance

#### HARDWARE FUNCTIONS

- Interface 1 micro USB port for power supply
- 1 micro SIM card slot
- 1 micro SD card slot
- Flavour Power menu
- Power supply 3000mAh battery
- Network type FDD-LTE: B1/B3/B7/B8/B20 (2100/1800/2600/900/800 MHz) TDD-LTE: B38/B40/B41 (2600/2300/2500 MHz)
- DC-HSPA+/HSPA/UMTS: B1/ B8 (2100/900 MHz)
- EDGE/GPRS/GSM: 850/900/1800/1900 MHz
- Data rates Download: 600 Mbit/s
- Upload: 50 Mbit/s
- Dimensions (W\*D\*H) 112,5mm\*66,5mm\*16mm
- Antenna Practitioner
- Micro SD card reader Up to 32GB
- Display 1.44-inch, TFT

#### WIFI FUNCTIONS

- WLAN standards IEEE802.11a/b/g/n/ac,
- 300Mbit/s on 2.4GHz or 867Mbit/s on 5GHz
- Frequency 2.4GHz
- 5GHz
- Transmission power 2.4GHz: max. 20dBm
- 5GHz: max. 23dbm
- WLAN security WPA-PSK/WPA2-PSK
- MAC address filtering

#### OTHER

- Certification CE-RoHS
- Package contents: Advanced 600Mbps LTE Mobile WLAN Router M7650; Micro-USB cable; Nano-to-Micro SIM adapter; 3000mAh battery; Quick installation guide
- System Requirements Windows 10/8/7/Vista/XP, Mac OS, Android, iOS, Windows Phone

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

