

Item no.: 343562

WH66 MONO UC - UC Workstation DECT Wireless Headset

from **245,75 EUR**

Item no.: 343562
 shipping weight: 1.10 kg
 Manufacturer: Yealink



Product Description

WH66 Mono UC - UC Workstation DECT Wireless Headset

The Yealink WH66 is an industry-leading DECT wireless headset, available as WH66 Dual and WH66 Mono, opening an entirely new form of desktop collaboration. It works seamlessly with major UC platforms and integrates natively with Yealink IP phones. The 4.0 inch (480 x 800) capacitive touch screen of the base offers a completely new work experience as you have full control just by one touch. It acts as a workstation, managing phone calls, connecting with multiple devices (desk phone/mobile phone/computer), charging mobile phones wirelessly, and even playing a speakerphone's role. Best of all, deploying such a multifunctional workstation only needs direct plugging. The easiest things to do, the greatest convenience to enjoy.

- 4.0 inch (480 x 800) capacitive touch screen
- 2x feature buttons
- 1x type-A USB 3.0 port
- Built-in Bluetooth 4.2
- Connectivity: USB 3.0 & 2x Bluetooth devices
- Integrated busylight LED indicator
- Built-in hub: 2x type-A USB 3.0 ports
- Boom arm adjustable: 320°
- Charging stand (for headset)

Battery

- Talk time: Up to 13 hours (Mono), up to 14 hours (Dual)
- Standby time: 90 hours (Mono), 125 hours (Dual)
- Charging time: 2.5 hours (12 V/2 A)

DECT

- Wireless range: Up to 160 m/525 feet
- Secure DECT (level): Step C: Authentication – DSAA2, encryption – DSC2 (128 bit)
- Cordless Advanced Technology: CAT-iq 2.0

Audio (Headset)

- Microphone type: Dual microphone
- Microphone sensitivity: -44.0+/-3 dBV
- Microphone frequency range: 100 Hz-10 kHz
- Speaker size: ? 28
- Speaker sensitivity: 92.5+/-3 dB, 0.179 V
- Speaker impedance: 32+/-4.8 ?
- Speaker max. output power: 10 mW
- Speaker frequency range: 20 Hz - 20 kHz
- Speaker bandwidth - talk mode: Wideband, 100 Hz - 8 kHz
- Speaker bandwidth - music mode: Super wideband, 20 Hz - 20 kHz (pending)
- Hearing protection: Peak Block Protection (EN50332), Australian G616 Protection (AU G616), Daily Noise Exposure Protection

Audio (Base)

- Microphone type: ECM omnidirectional microphone
- Microphone sensitivity: -38.0+/-2 dBV
- Microphone frequency range: 70 Hz - 20 kHz
- Speaker size: 40 x 20.8 mm
- Speaker sensitivity: 97+/-3 dB
- Speaker impedance: 4 ?+/-15%
- Speaker max. output power: 4 W
- Speaker frequency range: 160 Hz - 20 kHz

Easy Call Management

- Answer/end/reject a call
- Volume up/down
- Microphone mute
- Move the microphone boom arm up to mute, or down to unmute

Package Features

- Package contents: WHB660 base, WHM621 or WHD622 headset, power adapter, 2x 1 m USB 3.0 cable, quick start guide
- Optional accessories: Busylight BLT60, wireless charger, Bluetooth dongle BT50
- Carton measurements: 698 x 421 x 265 mm

Specifications

**Scan this QR code to
view the product**
All details, up-to-date
prices and availability

