

Item no.: 343549

SIP-T33G - Entry-level IP Phone with 4 Lines & Color LCD

from **79,58 EUR**

Item no.: 343549
shipping weight: 1.00 kg
Manufacturer: Yealink



Product Description

SIP-T33G - Entry-level IP Phone with 4 Lines & Color LCD

An entry-level color screen IP phone with high performance, Yealink SIP-T33G offers support for 4 lines and includes local 5-way conferencing. For its fashionable appearance as well as an extra-large 320x240-pixel color display with backlight, it brings comfortable operation experience and clear visual experience for users. Designed with a new powerful chip, it helps greatly improve work efficiency. Additional features include a dual-port Gigabit Ethernet with integrated PoE, EHS35 support for Yealink wireless headset, and adjustable multi-angle stand support. These features allow the SIP-T33G to be a high-quality but cost-effective classic IP phone that maximizes productivity in both small and large office environments.

Audio Features

- HD voice: HD handset, HD speaker
- Smart Noise Filtering
- Wideband codec: Opus, G.722
- Narrowband codec: G.711(A/?), G.723.1, G.729, G.729A, G.726, iLBC
- DTMF: In-band, Out-of-band (RFC 2833) and SIP Info
- Full-duplex hands-free speakerphone with AEC
- VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

- 4x VoIP accounts
- Call hold, mute, DND
- One-touch speed dial, hotline
- Call forward, call waiting, call transfer
- Group listening, SMS, emergency call
- Redial, call return, auto answer
- Local 5-way conferencing
- Direct IP call without SIP proxy
- Ring tone selection/import/delete
- Set date time manually or automatically
- Dial plan
- XML browser, action URL/URI
- Integrated screenshots
- RTCP-XR, VQ-RTCPXR
- Enhanced DSS Key

Display and Indicator

- 2.4" 320 x 240-pixel color display with backlight
- 16 bit depth color
- LED for call and message waiting indication
- Dual-color (red or green) illuminated LEDs for line status information
- Wallpaper
- Intuitive user interface with icons and soft keys
- Multilingual user interface
- Caller ID with name and number
- Screensaver
- Power saving

Feature keys

- 4x line keys with LED
- 4x line keys can be programmed up to 12 paperless DSS keys (4-page view)
- 5x features keys: message, headset, redial, mute, hands-free speakerphone
- 6x navigation keys
- Volume control keys

Interface

- Dual-port Gigabit Ethernet
- Power over Ethernet (IEEE 802.3af), class 2
- 1x RJ9 (4P4C) handset port
- 1x RJ9 (4P4C) headset port

Other Physical Features

- Color: Classic grey
- Wall mountable
- External Yealink AC adapter AC 100~240 V input and DC 5 V/600 mA output
- Power consumption (PSU): 2-3 W
- Power consumption (PoE): 3.5-5 W
- Dimension (W x D x H): 212 x 186 x 146 mm
- Operating humidity: 10~95%
- Operating temperature: -10°C ~ 50°C (+14°F ~ 122°F)

Specifications

**Scan this QR code to
view the product**

All details, up-to-date
prices and availability

