

Item no.: 375104

## AWUS036AX - 11ax 2x2 AX1800 Wireless LAN USB 3.0 Dongle

from **22,49 EUR**

Item no.: 375104  
shipping weight: 0.20 kg  
Manufacturer: ALFA Network



### Product Description

The AWUS036AX USB adapter incorporates highly integrated Realtek™ RTL8832BU WLAN chipset, with support for 802.11ax standard. The device supports dual-band operation (2.4 GHz or 5 GHz band), is backward compatible (802.11a/b/g/n/ac) and includes two RP-SMA female connectors equipped with dual-band 5 dBi dipole omni antennas.

Key features- RTL8832BU WiFi 6 chipset- USB-A connector support USB 3.2 GEN 1- RP-SMA external antenna connector- High-gain dual-band 2.4 GHz +5 GHz detachable dipole antenna- LED indicator Specification- Chipset: Realtek™: RTL8832BU- IEEE 802.11 standards: a/b/g/n/ac/ax- Frequency: 2.4 GHz/5 GHz- Data rate 11b: 1, 2, 5.5, 11 Mbps 11a/g: 6, 9, 12, 18, 24, 36, 48 and 54 Mbps 11n: up to 300 Mbps 11ac: up to 866.7 Mbps 11ax 2.4 GHz: up to 573.5 Mbps 11ax 5 GHz: up to 1201 Mbps- USB connector: USB 3.2 Gen 1 Type-A- Wi-Fi Antenna: 2x RP-SMA antenna connector with 2x dual-band high-gain dipole antenna- Power consumption: 3.6 W (max.)- Dimensions: 87.4 x 28.5 x 12 mm (3.44 x 1.13 x 0.47 inches)- Operating temperature: -20°C - 70°C- Operation voltage: 5V- OS support: Windows 10/11 & Linux

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

