

Item no.: 384784

## UniFi 8 port GbE PoE Switch powered by PoE input, 60W power adapter included

from **141,31 EUR**

Item no.: 384784  
shipping weight: 0.70 kg  
Manufacturer: Ubiquiti



### Product Description

Mechanical: Dimensions: 203 x 76 x 33 mm (8 x 3 x 1.3") Weight: - Device: 320 g (11.3 oz)- Wall mount: 45 g (1.6 oz)- 60W adapter: 330 g (11.6 oz) Enclosure material: Polycarbonate Hardware Management interface: Ethernet In-Band Networking interface: (8) GbE RJ45 ports PoE interface: (7) PoE/PoE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 8 Gbps Switching capacity: 16 Gbps Power method: - (1) 54V, 1.1A power adapter (Included)- PoE++ (Pins 1, 2+; 3, 6- and 4, 5+; 7, 8-) Power supply: 54V, external, 1.1A/60W Supported voltage range: 44—57V DC Max. power consumption: - 9W with PoE input (Excluding PoE output)- 8W with AC adapter input (Excluding PoE output) Total available PoE: - PoE++ input: 42W- PoE+ input: 16W- 60W PoE adapter input: 42W- 60W AC adapter input: 52W- 210W AC adapter input: 202W\*\* At 45° C (113° F) operating temperature. Reduced to 161W (230V) or 121W (115V) at 60° C (140° F) Max. PoE+ wattage per port by PSE: 30W Button: Factory reset Ambient operating temperature: - PoE++ input: -30 to 60° C (-22 to 140° F)- 60W AC adapter input: -20 to 45° C (-4 to 113° F)- 210W AC adapter input: -20 to 60° C (-4 to 140° F) Ambient operating humidity: 10 to 90% noncondensing Certifications: CE, FCC, IC Switching Features Layer 2 features: - Port isolation- Storm control- Port mirroring- Multicast / broadcast rate limiting- Flow control- Jumbo frames- Egress rate limit Layer 3 features: - LEDs System: Status Ethernet: - PoE- Link/activity Application Requirements- UniFi Network: Version 8.0.7 and later

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

