

Item no.: 384510

AMT912LWS - QuSpot for Mikrotik RB912RB922 LTE Wi-Fi

from **93,53 EUR**

Item no.: 384510
 shipping weight: 1.50 kg
 Manufacturer: QuWireless



Product Description

Integrated multi-band LTE omni antenna + WiFi omni antenna + place to install MikroTik RB912 or RB922 (All-in-one) QuSpot omnidirectional LTE antenna for MikroTik RB9xx is a perfect outdoor device for mobile and fixed installations like CCTV, hotspots, industrial areas, campervans, ships etc. The set contains IP67, ABS enclosure, LTE MIMO 2x2 and Wi-Fi MIMO 2x2 antennas, RJ45 (Ethernet) port and mast/pole/wall mounting bracket. If you use MikroTik RB912 or RB922 with QuSpot antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure.

LTE ANTENNA SPECIFICATION
 FREQUENCY- 694 - 960 MHz- 1.7 - 2.2 GHz- 2.2 - 2.7 GHz
 SUPPORTED LTE/5G BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256
 GAIN- 694 - 960 MHz : 2 dBi- 1.7 - 2.2 GHz : 2 dBi- 2.2 - 2.7 GHz : 4 dBi
 VSWR- <1.60, max <2.00
 BEAMWIDTH- 360°/35° ±5°
 POLARIZATION- Vertical
 IMPEDANCE- 50 Ω

WI-FI ANTENNA SPECIFICATION
 FREQUENCY- 2.40 - 2.50 GHz- 5.0 - 7.125 GHz
 GAIN- 2.40 - 2.50 GHz : 6 dBi- 5.0 - 7.125 GHz VSWR- <1.70, max <2.00
 BEAMWIDTH- 360°/25° ±5°
 POLARIZATION- Vertical
 IMPEDANCE- 50 Ω

MECHANICAL SPECIFICATION
 MATERIALS- ABS, aluminum, PTFE
 CONNECTOR TYPE- RJ45
 INGRESS PROTECTION- IP67
 DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch
 WEIGHT- 1.5 kg- 3.31 lbs
 OPERATING TEMPERATURE- From -40°C to 80°C- From -40°F to 176°F
 MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

