

Item no.: 384510

## AMT912LWS - QuSpot for Mikrotik RB912RB922 LTE Wi-Fi

from **98,15 EUR**

Item no.: 384510  
 shipping weight: 1.50 kg  
 Manufacturer: QuWireless



### Product Description

Integrated multi-band LTE omni antenna + WiFi omni antenna + place to install MikroTik RB912 or RB922 (All-in-one) QuSpot omnidirectional LTE antenna for MikroTik RB9xx is a perfect outdoor device for mobile and fixed installations like CCTV, hotspots, industrial areas, campervans, ships etc. The set contains IP67, ABS enclosure, LTE MIMO 2x2 and Wi-Fi MIMO 2x2 antennas, RJ45 (Ethernet) port and mast/pole/wall mounting bracket. If you use MikroTik RB912 or RB922 with QuSpot antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure.

**LTE ANTENNA SPECIFICATION**  
 FREQUENCY- 694 - 960 MHz- 1.7 - 2.2 GHz- 2.2 - 2.7 GHz  
 SUPPORTED LTE/5G BANDS- 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 30, 33, 34, 35, 36, 37, 38, 39, 40, 41, 44, 53, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n90, n95, n97, n98, n100, n101, n256  
 GAIN- 694 - 960 MHz : 2 dBi- 1.7 - 2.2 GHz : 2 dBi- 2.2 - 2.7 GHz : 4 dBi  
 VSWR- <1.60, max <2.00  
 BEAMWIDTH- 360°/35° ±5°  
 POLARIZATION- Vertical  
 IMPEDANCE- 50 Ω

**WI-FI ANTENNA SPECIFICATION**  
 FREQUENCY- 2.40 - 2.50 GHz- 5.0 - 7.125 GHz  
 GAIN- 2.40 - 2.50 GHz : 6 dBi- 5.0 - 7.125 GHz VSWR- <1.70, max <2.00  
 BEAMWIDTH- 360°/25° ±5°  
 POLARIZATION- Vertical  
 IMPEDANCE- 50 Ω

**MECHANICAL SPECIFICATION**  
 MATERIALS- ABS, aluminum, PTFE  
 CONNECTOR TYPE- RJ45  
 INGRESS PROTECTION- IP67  
 DIMENSIONS- 160 x 160 x 240 mm- 6.3 x 6.3 x 9.45 inch  
 WEIGHT- 1.5 kg- 3.31 lbs  
 OPERATING TEMPERATURE- From -40°C to 80°C- From -40°F to 176°F  
 MAST DIAMETER- 40-60 mm- 1.57-2.36 inch

### Specifications

Scan this QR code to view the product  
 All details, up-to-date prices and availability

