

Item no.: 384320

## AR2110MOP - QuMax Omni with PoE Splitter for Robustel R2110

from **187,59 EUR**

Item no.: 384320  
shipping weight: 2.00 kg  
Manufacturer: QuWireless



### Product Description

**INTEGRATED MULTI-BAND LTE OMNI ANTENNA + WIFI OMNI ANTENNA + BLUETOOTH ANTENNA + GPS ANTENNA + PLACE TO INSTALL ROBUSTEL R2110 (ALL-IN-ONE)** QuMax Omni all-in-one antenna for Robustel R2110 router is a perfect outdoor device for mobile and fixed installations like industrial, public, CCTV, hotspots, yachts, boats, campers, RV etc. It has embedded omni LTE, Wi-Fi, Bluetooth and GPS antenna. If you use R2110 with QuMax Omni antenna, you get an integrated complete solution with embedded router and multi band antennas in one enclosure. Wi-Fi 7 support! Note! This antenna comes in two different versions, depending on your router configuration. When you use R2110 supporting Power over Ethernet (PoE) please choose version "no PoE splitter". For R2110 without PoE support, please choose "PoE splitter" version. Compatible Robustel part numbers available in the specification below.

**LTE SPECIFICATION**  
**FREQUENCY**- 0.694-0.96 GHz- 1.7 - 2.2 GHz- 2.5 - 2.7 GHz  
**SUPPORTED LTE/5G BANDS**- 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 23, 25, 26, 27, 28, 29, 33, 34, 35, 36, 37, 38, 39, 44, 59, 62, 65, 66, 67, 68, 69, 85, n80, n81, n82, n83, n84, n86, n89, n95  
**GAIN**- 0.694 - 0.96 GHz : 4 dBi- 1.7 - 2.2 GHz : 5 dBi- 2.5 - 2.7 GHz : 6 dBi  
**SWR**- <1.50, max <2.50  
**BEAMWIDTH**- 360°/25° +/- 5°  
**POLARIZATION**- Vertical  
**IMPEDANCE**- 50 Ω  
**WI-FI SPECIFICATION**  
**FREQUENCY**- 2.4 - 2.5 GHz- 4.7 - 6.0 GHz  
**GAIN**- 2.4 - 2.5 GHz: 6 dBi- 4.7 - 6.0 GHz: 7 dBi  
**SWR**- <1.70, max <2.00  
**BEAMWIDTH**- 360°/25° +/- 5°  
**POLARIZATION**- Vertical  
**IMPEDANCE**- 50 Ω  
**MECHANICAL SPECIFICATION**  
**MATERIAL**- BS, aluminum, PTFE, Fiberglass  
**INGRESS PROTECTION**- IP67  
**CONNECTOR TYPE**- RJ45  
**DIMENSIONS**- 272 x 276 x 96 mm- 10.71 x 10.87 x 3.78 inch  
**WEIGHT**- 1.8 kg- 3.97 lbs  
**OPERATING TEMPERATURE**- From -40°C to 75°C- From -40°F to 167°F  
**MOUNTING KIT**  
**DIMENSIONS**- 9.9 x 10.5 x 14.8 cm- 3.9 x 4.13 x 5.83 inch  
**REGULATION RANGE**- +/- 30°  
**MAST DIAMETER RANGE**- 25 - 60mm- 0.98-2.36 inch  
**MATERIAL**- Polyamide with fiberglass + galvanized steel U-Bolts  
**WEIGHT**- 0.87kg  
**MOUNTING PLACE**- Wall or mast or ceiling

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

