

Item no.: 384347

## AOLO1 - QuOmni 4GLTE SISO, Nm

from **33,11 EUR**

Item no.: 384347  
shipping weight: 0.50 kg  
Manufacturer: QuWireless



### Product Description

QuOmni 4G/LTE Nm offers a 360 degrees, 4dBi gain signal. It is a perfect indoor and outdoor device for industrial installations. QuOmni 4G/LTE Nm is a 4G and LTE, Vertical polarity, omni antenna. It with up to 4dNbi gain. This antenna is predicted to be installed as the hotspot in parks, stadiums, warehouses, production halls, malls, lecture halls or another public places. Its aesthetic design is acceptable in most of the visible places. Wide frequency range helps to find suitable frequency for the most effective operation. The antenna comes with built-in Nm connector. LTE antenna specification

| FREQUENCY              | 694 - 960 MHz  | 1.7 - 2.2 GHz         | 2.2 - 2.7 GHz         |
|------------------------|--|-----------------------|-----------------------|
| SUPPORTED LTE/5G BANDS | 1, 2, 3, 4, 5, 7, 8, 9, 10, 12, 13, 14, 17, 18, 19, 20, 25, 26, 27, 28, 29, 33, 34, 35, 36, 37, 38, 39, 44, 65, 66, 67, 68, 69, 85, 103, n80, n81, n82, n83, n84, n86, n89, n95, n98, n100, n101, n256 |                       |                       |
| GAIN                   | 694 - 960 MHz : 2 dBi  | 1.7 - 2.2 GHz : 2 dBi | 2.2 - 2.7 GHz : 3 dBi |
| SWR                    | <1.50, max <2.50   |                       |                       |
| BEAMWIDTH              | 360°/25° ±5°   |                       |                       |
| POLARIZATION           | Vertical   |                       |                       |
| IMPEDANCE              | 50 Ω   |                       |                       |
| MATERIAL               | ABS  |                       |                       |
| CONNECTOR TYPE         | N male   |                       |                       |
| DIMENSIONS             | ø3.0 x 22.0 cm- ø1.18 x 8.66 inch  |                       |                       |
| WEIGHT                 | 0.2 kg   |                       |                       |
| OPERATING TEMPERATURE  | From -40°C to 80°C- From -40°F to 176°F  |                       |                       |

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

