

Item no.: 384798

UVC-G5-BULLET-3 - Next-gen 2K HD PoE camera that can be deployed indoors or outside, 3-pack

from **369,87 EUR**

Item no.: 384798
shipping weight: 0.30 kg
Manufacturer: Ubiquiti

Product Description

Next-gen indoor/outdoor 2K HD PoE Camera. Details- 2K (4MP) video resolution- Flexible 3-axis adjust mount- 9 m (30 ft) IR night vision- AI event detections- Record audio with an integrated microphone- Connect and power using PoE- Weatherproof (outdoor exposed) Mechanical- Dimensions Without mount: Ø75.5 x 74.4 mm (Ø3 x 2.9") With mount: Ø75.5 x 150 mm (Ø3 x 5.9")- Weight Without mount: 225 g (8 oz) With mount: 315 g (11.1 oz)- Enclosure material Polycarbonate, aluminum alloy- Mount material Wall mount: aluminum alloy, polycarbonate Pole mount: aluminum alloy- Weatherproofing IP55- Resistance IK04 Optics- Sensor 5MP CMOS- Lens Fixed focal length- View angle H: 84.4°, V: 45.4°, D: 99.8°- Night mode Built-in IR LED illumination and IR cut filter Video- Video compression H.264- Resolution 4MP 2688 x 1512 (16:9)- Max. frame rate 30 FPS- Image settings Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay System- Processor Dual-core Arm® Cortex®-A7 based chip- Networking interface 10/100 MbE RJ45 port- Max. power consumption 4W- Power method PoE- Supported voltage range 37—57V DC- Button Factory reset- Mounting Wall, pole mount- Ambient operating temperature -20 to 40° C (-4 to 104° F)- Ambient operating humidity 0 to 90% noncondensing- Certifications FCC, IC, CE Audio- Microphone Yes (Can be disabled) Software- Web application UniFi Protect: Version 2.2.7 or 2.7.28 and later- Mobile app UniFi Protect iOS™ and Android™: Version 1.10.0 and later

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

