

Item no.: 344131

## BU650EU - UPS, 650 VA/360 W, AVR, 3x Schuko

from **80,49 EUR**

Item no.: 344131  
shipping weight: 4.00 kg  
Manufacturer: CyberPower



### Product Description

#### BU650EU - UPS, 650 VA/360 W, AVR, 3x Schuko

CyberPower BU650EU provides home and office users with a reliable battery backup and safeguards office PCs and other electronic devices from surges, spikes, brownouts and other power irregularities. As all CyberPower UPSs are designed with fireproof plastic housing, this product provides an outstanding fire-resistant capability (as compared to similar products) to minimize possible damage to valuable assets in case of fire.

The innovative Battery Management Technology significantly increases battery efficiency and promotes increased battery performance and longer battery life. Configurable alarm allows users to switch the audible alarm on or off during battery mode to avoid unnecessary disturbances. Its desktop design with mounting slots allows users to place it easily on walls, desks or other tight spaces.

#### General

- Phase: Single phase
- Form factor: Desktop
- UPS topology: Line-interactive

#### Input

- Generator compatibility: Yes
- Nominal input voltage (Vac):  $230 \pm 10\%$
- Input voltage range (Vac): 165 ~ 280
- Input frequency (Hz):  $50 \pm 5$ ;  $60 \pm 5$
- Input frequency detection: Auto-sensing
- Rated input current (A): 2.95
- Input connector type: Schuko
- Power cord length (ft.): 4
- Power cord length (m.): 1.2

#### Output

- Capacity (VA): 650
- Capacity (Watts): 360
- On battery waveform: Simulated sine wave
- On battery voltage(s) (Vac):  $230 \pm 10\%$
- On battery frequency (Hz):  $50 \pm 1\%$ ;  $60 \pm 1\%$
- Automatic voltage regulation (AVR): Single boost, single buck
- Overload protection: Fuse
- Outlet(s), total: 3
- Outlet type: 3x Schuko
- Outlet(s), battery & surge protected: 3
- Typical transfer time (ms): 4

#### Battery

- Runtime at 60 W (min.): 30
- Runtime at 90 W (min.): 18
- Typical recharge time (hours): 8
- Start on battery: Yes
- User-replaceable: No
- Battery type: Sealed lead-acid

#### Surge Protection & Filtering

- Surge suppression (Joules): 150
- EMI/RFI filtration: Yes

#### Management & Communication

- LED indicators: Power on, line mode, battery mode, low battery
- HID compliant USB port(s): 1
- Audible alarms: Battery mode, low battery, overload, UPS fault
- Management cable (pcs.): 1x USB cable
- Power management software: PowerPanel® Personal (recommended)

#### Physical

- Wall mount installation: Yes
- Enclosure construction: Plastic
- Color: Black

#### Physical Size - UPS Module

- Dimensions (WxHxD, in.): 6.33 x 3.6 x 9.45
- Dimensions (WxHxD, mm.): 158 x 91.5 x 240
- Weight (lbs.): 8.38
- Weight (kg.): 3.8

#### Environment

- Operating temperature (°F): 32 ~ 104
- Operating temperature (°C): 0 ~ 40
- Operating relative humidity (non-condensing, %): 0 ~ 90
- Operating elevation (feet/meters): 0-9,843 feet (0-3,000 meters)
- Storage temperature (°F): -4 ~ 122
- Storage temperature (°C): -20 ~ 50
- Storage relative humidity (non-condensing, %): 0 ~ 90
- Storage elevation (feet/meters): 0-9,843 feet (0-3,000 meters)
- Online thermal dissipation (BTU/hr): 40
- Audible noise at 1.5 m from surface of unit (dBA): 40

#### Certifications

- Certifications: CE
- RoHS: Yes

## Specifications

---

**Scan this QR code to  
view the product**  
All details, up-to-date  
prices and availability

