

Item no.: 385516

UPOINT 407 - 7-port industrial USB hub, adaptor included, 0 to 60C operating temperature

from **285,21 EUR**

Item no.: 385516
shipping weight: 1.00 kg
Manufacturer: MOXA



Product Description

The UPOINT series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPOINT Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions. USB Interface- Speed 12 Mbps, 480 Mbps- USB Connector USB Type B- USB Standards USB 1.1/2.0 compliant- No. of USB Ports 7 Power Parameters- Input Current 2.3 A @ 12 VDC- Input Voltage 12 to 40 VDC Physical Characteristics- Housing Aluminum- Dimensions 100 x 35 x 192 mm (3.94 x 1.38 x 7.56 in)- Weight Packaged: 965 g (2.13 lb) Product only: 950 g (2.1 lb)- Installation Wall mounting, DIN-rail mounting (optional) Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -20 to 75°C (-4 to 167°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 0 V/m IEC 61000-4-8 PFMF- Environmental Testing IEC 60068-2-1- Safety UL 508- Freefall IEC 60068-2-34 Declaration- Green Product RoHS, CRoHS, WEEE MTBF- Time 1,111,361 hrs- Standards Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

