

Item no.: 385954

## VPORT P06-1MP-M12-MIC-CAM36-CT - EN50155, HD, compact IP camera, M12 connection

from **734,79 EUR**

Item no.: 385954  
shipping weight: 0.40 kg  
Manufacturer: MOXA



### Product Description

Our range of IP cameras includes dome and box cameras as well as cameras with a robust design. They fulfil parts of the EN 50155 standard, providing reliable performance and excellent image quality suitable for a range of applications. Ethernet interface- PoE connections (10/100BaseT(X), M12 D-coded 4-pin socket) Ethernet software features- Protocols TCP/IP IPv4 UDP HTTP RTP/RTSP ARP UPnP FTP TFTP NTP client DNS QoS IGMP v3 ICMP SNMP v1/v2c/v3 DHCP Opt66/67 HTTP Security functions- Password Password Password protection at user level- Filter IP address- Encryption HTTP Performance parameters- Number of power inputs 1- Power source PoE (IEEE 802.3af)- Input current 0.12 A @ 48 VDC Camera features- Sensor 1/2.7-in HD progressive scan CMOS- Lens f=3.6 mm, F1.6, diagonal 99°, horizontal 94°, vertical 47°- Camera angle pan: ±30°, tilt: 0° to 90° (manually controlled)- Minimum illumination colour: 0.2 lux, at F1.2 (Gain High, 50 IRE, 1/30 sec.)- Synchronisation Internal- White balance ATW/AWB- Electronic shutter Auto, fixed (1/30 to 1/25000 sec.)- S/N Ratio Maximum 50 dB (AGC off; DNR on)- DNR (Digital Noise Reduction) Built-in 2D/3D DNR- WDR (Wide Dynamic Range) 110 dB- Flickerless Control Automatic, 50 Hz, 60 Hz modes- Image rotation Flip, Mirror, and 180° rotation- Image adjustment Manual adjustment with saturation, sharpness and contrast- AGC (automatic gain control) 2X, 4X, 8X, 16X, 32X, 64X- BLC (backlight compensation) High/Medium/Low Video interface- Video compression H.264 (ISO/IEC 14496-10) or MJPEG- Video output via Ethernet- Video streams 3 independent H.264 or MJPEG video streams- Video viewing DynaStream™ support for automatically changing the video frame rate CBR Pro™ for good image quality for transmissions with limited bandwidth 3 privacy mask areas available Adjustable image size and quality Timestamp and text overlay OSD (On Screen Display) position adjustable Maximum 5 simultaneous unicast connections, 50 multicast clients Audio interface- Audio inputs 1 x built-in microphone- Audio format mono, PCM (G.711) Camera software development- Video standards ONVIF profile S Camera alarm software functions- Intelligent video camera manipulation detection- Video motion detection 3 independently configurable areas- Scheduling Daily schedule repetition- Imaging JPEG snapshots for pre/trigger/post-alarm images/Post-alarm images- Custom alarms HTTP event server for setting custom alarm actions- FTP messaging Automatic transfer of stored images via FTP as event-triggered actions Software requirements- Memory size 1 GB- Operating system Windows 7 or higher- Browser Internet Explorer 9.x or higher- Multimedia DirectX 9.0C or higher Physical properties- Housing Plastic top cover, metal base plate IP66 protection against rain and dust IK10 protection against vandalism Transparent PC cover- Dimensions 110 x 47 mm (4.33 x 1.85 in)- Weight 310 g (0.68 lb)- Panel mounting installation- PCB protective coating

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

