

Item no.: 356378

TP-Link LS105G LiteWave 5-Port Gigabit Desktop Switch

from **14,34 EUR**

Item no.: 356378
shipping weight: 0.40 kg
Manufacturer: TP-LINK



Product Description

The TP-Link 5-port 10/100/1000Mbps desktop switch from the new TP-Link LiteWave series offers an easy way to expand your network. Thanks to the plug-and-play design, the product is easy to use. No configuration is required. In addition, Auto MDI / MDIX eliminates the need for crossover cables. This LiteWave series features the latest innovative energy-efficient technologies that allow you to significantly expand your network capacity. You now have the option to go green when upgrading to a Gigabit network. It automatically adjusts power consumption based on connection status and cable length to limit your network's carbon footprint. Not only energy consumption but also your costs are reduced. The LS105G has a high-quality metal housing to ensure a long service life. The LS105G has passed a series of rigorous reliability tests and offers switching performance you can rely on. The design can be used for easy desktop or wall mounting. High quality metal. The LS105G is compatible with almost all network devices, e.g. computers, printers, webcams and IPTVs. The switch is used in a wide range of applications and is the environmentally friendly solution for your home or business network.

HARDWARE FUNCTIONS- Standards and protocols: IEEE 802.3i/802.3u/ 802.3ab/802.3x, IEEE 802.1p- Interface: 5 10/100/1000Mbps, auto-negotiation, auto-MDI/MDIX ports- Number of fans: Fanless- External power supply: External power adapter (output: 5VDC / 0.6A)- LEDs: System Power; Link/Act indicators per port integrated in each RJ-45 port- Dimensions (W*D*H): 3.9 x 3.9 x 1.0 in. (99.8 x 98 x 25 mm)- Maximum power consumption: 2,776W (220V/50Hz)- Maximum heat dissipation: 9,466 BTU/h**PERFORMANCE-** Packet forwarding rate: 7.4 Mpps- MAC address table: 2K- Packet buffer memory: 1 Mb- Jumbo frames: 16 KB**SOFTWARE FEATURES-** Advanced features: Green technology; 802.3X flow control; 802.1P/DSCP QoS- Transmission Method: Store and Forward**OTHER-** Certification: CE, FCC, RoHS- Package Contents: 5-Port 10/100/1000Mbps Desktop Switch; Power Adapter; Installation Manual- Environment: Operating temperature: 0°C-40°C (32°F-104°F); Storage temperature: -40°C-70°C (-40°F-158°F); Operating humidity: 10%-90% non-condensing; Storage humidity: 5%-90% non-condensing

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

