

Item no.: 387315

## UA-LOCK-MAGNETIC-540KG - Magnetic lock for swing-in and swing-out doors, for UniFi Access Hub

from **200,93 EUR**

Item no.: 387315  
shipping weight: 0.30 kg  
Manufacturer: Ubiquiti



### Product Description

Fail-safe magnetic lock for swing-in and swing-out doors, which is connected to a UniFi Access Hub (UA Hub).  
Technical data  
Mechanical- Dimensions  
UA-Lock-Magnetic-270kg  
Lock body: 250 x 42.5 x 26 mm (9.8 x 1.7 x 1")  
Installation plate: 250 x 25 x 5 mm (9.8 x 1 x 0.2")  
Anchor: 185.5 x 38.5 x 11 mm (7.3 x 1.5 x 0.4")  
UA-Lock-Magnetic-540kg  
Lock body: 266 x 67.5 x 40 mm (10.5 x 2.7 x 1.6")  
Mounting plate: 266 x 40 x 6 mm (10.5 x 1.6 x 0.2")  
Anchor: 185 x 61 x 16 mm (7.3 x 2.4 x 0.6")  
Weight  
UA-Lock-Magnetic-270kg  
Lock body: 1 kg (2.2 lb)  
Mounting plate: 70 g (0.15 lb)  
Anchor: 600 g (1.3 lb)  
UA-Lock-Magnetic-540kg  
Lock body: 2.9 kg (6.4 lb)  
Mounting plate: 145 g (0.3 lb)  
Fitting: 1.4 kg (3.1 lb)  
Housing material  
Device/brackets: Aluminium  
Armature: Steel  
Hardware- Voltage: 12V DC- Current  
UA-Lock-Magnetic-270kg: 800mA  $\pm$ 10%,  
UA-Lock-Magnetic-540kg: 500mA  $\pm$ 10%- Wiring connection: Connect the following terminals to the UA-Hub:  
Lock 12V/NC (connect the Power Lock relay NC to the UA-Hub)  
Lock 12V/COM (connect the Powered Lock relay COM to the UA-Hub)  
DPS/+ (DPS+ to the UA-Hub)  
DPS/- (DPS- to the UA-Hub)- Lock type: Fail-safe lock, single door- Holding force:  
UA-Lock-Magnetic-270kg: 270 kg (600 lb), UA-Lock-Magnetic-540kg: 540 kg (1.200 lb)- LED  
Green: unlocked  
Red: locked- Suitability: UA-Lock-Magnetic-270kg: wood/metal/glass door, UA-Lock-Magnetic-540kg: wood/metal door- Mounting accessories  
UA-Lock-Magnetic-270kg  
L-bracket : door thickness < 42 mm (< 1.7"), outward-opening door  
Z-bracket: used with L-bracket for inward-opening door  
U-bracket: used with glass door  
UA-Lock-Magnetic-540kg  
L-bracket: door thickness < 42 mm (< 1.7"), outward-opening door  
Z-mount: used with L-mount for inward-opening door- Operating environment: Temperature -10 to 50° C (14 to 122° F)- Operating environment: Humidity 5 to 90% non-condensing-  
Certifications: FCC, IC, CE

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

