

Item no.: 387315

UA-LOCK-MAGNETIC-540KG - Magnetic lock for swing-in and swing-out doors, for UniFi Access Hub

from **211,89 EUR**

Item no.: 387315
shipping weight: 0.30 kg
Manufacturer: Ubiquiti



Product Description

Fail-safe magnetic lock for swing-in and swing-out doors, which is connected to a UniFi Access Hub (UA Hub).
Technical data
Mechanical- Dimensions
UA-Lock-Magnetic-270kg
Lock body: 250 x 42.5 x 26 mm (9.8 x 1.7 x 1")
Installation plate: 250 x 25 x 5 mm (9.8 x 1 x 0.2")
Anchor: 185.5 x 38.5 x 11 mm (7.3 x 1.5 x 0.4")
UA-Lock-Magnetic-540kg
Lock body: 266 x 67.5 x 40 mm (10.5 x 2.7 x 1.6")
Mounting plate: 266 x 40 x 6 mm (10.5 x 1.6 x 0.2")
Anchor: 185 x 61 x 16 mm (7.3 x 2.4 x 0.6")
Weight
UA-Lock-Magnetic-270kg
Lock body: 1 kg (2.2 lb)
Mounting plate: 70 g (0.15 lb)
Anchor: 600 g (1.3 lb)
UA-Lock-Magnetic-540kg
Lock body: 2.9 kg (6.4 lb)
Mounting plate: 145 g (0.3 lb)
Fitting: 1.4 kg (3.1 lb)
Housing material
Device/brackets: Aluminium
Armature: Steel
Hardware- Voltage: 12V DC- Current
UA-Lock-Magnetic-270kg: 800mA \pm 10%,
UA-Lock-Magnetic-540kg: 500mA \pm 10%- Wiring connection: Connect the following terminals to the UA-Hub:
Lock 12V/NC (connect the Power Lock relay NC to the UA-Hub)
Lock 12V/COM (connect the Powered Lock relay COM to the UA-Hub)
DPS/+ (DPS+ to the UA-Hub)
DPS/- (DPS- to the UA-Hub)- Lock type: Fail-safe lock, single door- Holding force:
UA-Lock-Magnetic-270kg: 270 kg (600 lb), UA-Lock-Magnetic-540kg: 540 kg (1.200 lb)- LED
Green: unlocked
Red: locked- Suitability: UA-Lock-Magnetic-270kg: wood/metal/glass door, UA-Lock-Magnetic-540kg: wood/metal door- Mounting accessories
UA-Lock-Magnetic-270kg
L-bracket : door thickness < 42 mm (< 1.7"), outward-opening door
Z-bracket: used with L-bracket for inward-opening door
U-bracket: used with glass door
UA-Lock-Magnetic-540kg
L-bracket: door thickness < 42 mm (< 1.7"), outward-opening door
Z-mount: used with L-mount for inward-opening door- Operating environment: Temperature -10 to 50° C (14 to 122° F)- Operating environment: Humidity 5 to 90% non-condensing-
Certifications: FCC, IC, CE

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

