

Item no.: 386134

EDS-508A-MM-SC - Managed Ethernet switch with 6 10100BaseT(X) ports, 2 100BaseFX multi-mode ports

from **1.067,01 EUR**

Item no.: 386134
shipping weight: 0.40 kg
Manufacturer: MOXA



Product Description

Managed Ethernet switch with 6 10/100BaseT(X) ports, 2 100BaseFX multi-mode ports with SC connectors, 0 to 60°C operating temperature Input/Output Interface Alarm Contact Channels- 2- Relay output with current carrying capacity of 1 A @ 24 VDC Digital Input Channels- 2 Digital Inputs- +13 to +30 V for state 1- -30 to +3 V for state 0- Max. input current: 8 mA Ethernet Interface 10/100BaseT(X) Ports (RJ45 connector)- 6- Auto negotiation speed- Full/Half duplex mode- Auto MDI/MDI-X connection 100BaseFX Ports (multi-mode SC connector)- 2 Standards- IEEE 802.3 for 10BaseT- IEEE 802.3u for 100BaseT(X) and 100BaseFX- IEEE 802.1X for authentication- IEEE 802.1D-2004 for Spanning Tree Protocol- IEEE 802.1w for Rapid Spanning Tree Protocol- IEEE 802.1s for Multiple Spanning Tree Protocol- IEEE 802.1Q for VLAN Tagging- IEEE 802.1p for Class of Service- IEEE 802.3x for flow control- IEEE 802.3ad for Port Trunk with LACP Ethernet Software Features Filter- 802.1Q VLAN- Port-based VLAN- IGMP v1/v2- GVRP- GMRP Industrial Protocols- EtherNet/IP- Modbus TCP Management- IPv4/IPv6- SNMPv1/v2c/v3- LLDP- Port Mirror- Back Pressure Flow Control- BOOTP- DDM- DHCP Option 66/67/82- DHCP Server/Client- Flow control- RARP- RMON- SMTP- SNMP Inform- Syslog- Telnet- TFTP MIB- MIB-II- Bridge MIB- Ethernet-like MIB- P-BRIDGE MIB- Q-BRIDGE MIB- RMON MIB Groups 1, 2, 3, 9- RSTP MIB Redundancy Protocols- STP- MSTP- RSTP- LACP- Link Aggregation- Turbo Chain- Turbo Ring v1/v2 Security- HTTPS/SSL- TACACS+- Port Lock- RADIUS- SSH Time Management- NTP Server/Client- SNTP- IEEE 1588v2 PTP (software-based) Switch Properties IGMP Groups- 256 MAC Table Size- 8 K Max. No. of VLANs- 64 Packet Buffer Size- 1 Mbits Priority Queues- 4 VLAN ID Range- VID 1 to 4094 LED Interface LED Indicators- PWR1, PWR2, FAULT, 10/100M (TP port), 100M (fiber port), MSTR/HEAD, CPLR/TAIL Serial Interface Console Port- RS-232 (Tx, Rx, GND), 10-pin RJ45 (115200, n, 8, 1) DIP Switch Configuration Ethernet Interface- Turbo Ring, Master, Coupler, Reserve Power Parameters Connection- 2 removable 6-contact terminal block(s) Input Voltage- 12/24/48 VDC- Redundant dual inputs Operating Voltage- 9.6 to 60 VDC Input Current- 0.30 A @ 24 VDC Overload Current Protection- Supported Reverse Polarity Protection- Supported Physical Characteristics Housing- Metall IP Rating- IP30 Dimensions- 80.2 x 135 x 105 mm (3.16 x 5.31 x 4.13 in) Weight- 1040 g (2.3 lb) Installation- DIN-rail mounting- Wall mounting (with optional kit) Environmental Limits Operating Temperature- -10 to 60°C (14 to 140°F) Storage Temperature (package included)- -40 to 85°C (-40 to 185°F) Ambient Relative Humidity- 5 to 95% (non-condensing) Standards and Certifications Safety- EN 62368-1- UL 60950-1- UL 508 EMC- EN 55032/35 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 20 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 2 kV- IEC 61000-4-6 CS: 10 V- IEC 61000-4-8 PFMF Hazardous Locations- ATEX- Class I Division 2 Vibration- IEC 60068-2-6 Shock- IEC 60068-2-27 Freefall- IEC 60068-2-31 Maritime- DNVMTBF Time- 1,043,909 hrs Standards- Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

