

Item no.: 386068

## IMC-101-M-ST-IEX - Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector,

from **261,45 EUR**

Item no.: 386068  
shipping weight: 0.70 kg  
Manufacturer: MOXA



### Product Description

Moxa's Ethernet to Fiber media converters feature innovative remote management, industrial-grade reliability, and a flexible, modular design that can fit any type of industrial environment. Industrial 10/100BaseT(X) to 100BaseFX media converter, multi-mode, ST connector, IECEx, 0 to 60°C operating temperature Ethernet Interface- 10/100BaseT(X) Ports (RJ45 connector) 1- 100BaseFX Ports (multi-mode ST connector) 1- Magnetic Isolation Protection 1.5 kV (built-in) Power Parameters- Input Current 200 mA @ 12 to 45 VDC- Input Voltage 12 to 45 VDC- Overload Current Protection Supported- Power Connector Terminal block- Power Consumption 200 mA @ 12 to 45 VDC Physical Characteristics- IP Rating IP30- Housing Metal- Dimensions 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)- Weight 630 g (1.39 lb)- Installation DIN-rail mounting Environmental Limits- Operating Temperature 0 to 60°C (32 to 140°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m IEC 61000-4-8 PFM IEC 61000-4-11- Environmental Testing IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-3- Safety EN 60950-1, UL 60950-1- Vibration IEC 60068-2-6- Hazardous Locations ATEX Zone 2, UL/cUL Class I Division 2 Groups A/B/C/D, IECEx- Maritime DNVMTBF- Time 401,000 hrs- Standards MIL-HDBK-217F

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

