

Item no.: 386214

## IMC-101G-T - Industrial 101001000BaseT(X) to 1000BaseSXLXLHXZX media converter, -40 to 75C op

from **474,93 EUR**

Item no.: 386214  
shipping weight: 0.30 kg  
Manufacturer: MOXA



### Product Description

Ethernet interface 10/100/1000BaseT(X) ports (RJ45 connector)- 11000 Mbps optical fibre (SFP connector)- 1Magnetic isolation protection- 1.5 kV (built-in)Performance parametersInput current- 200 mA @ 12 to 45 VDCInput voltage- 12 to 45 VDCOverload current protection- SupportedPower connection- Terminal blockPower consumption- 200 mA @ 12 to 45 VDCPhysical characteristicsHousing- MetalDimensions- 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 in)Weight- 630 g (1.39 lb)Installation- DIN rail mountingAmbient conditionsOperating temperature- -40 to 75°C (-40 to 167°F)Storage temperature (including packaging)- -40 to 85°C (-40 to 85°C) -40 to 85°C (-40 to 185°F)Relative humidity- 5 to 95% (non-condensing)Standards and certificationsEMC- EN 55032/24EMI- CISPR 32, FCC Part 15B Class AEMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11Environmental testing- IEC 60068-2-1- IEC 60068-2-2- IEC 60068-2-3Safety- EN 60950-1, UL 60950-1Vibration- IEC 60068-2-6Hazardous areas- UL/cUL Class I Division 2 Groups A/B/C/DMTBFTime- 500.540 hoursStandards- Telcordia (Bellcore), GB

### Specifications

Scan this QR code to  
view the product  
All details, up-to-date  
prices and availability

