

Item no.: 386086

IMC-21GA-SX-SC - Industrial 101001000BaseT(X) to 1001000Base SC media converter, 0.5 km

from **258,64 EUR**

Item no.: 386086
shipping weight: 0.30 kg
Manufacturer: MOXA



Product Description

Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 0.5 km, -10 to 60°C Operating temperature Ethernet interface 10/100/1000BaseT(X) ports (RJ45 connector)- 11000BaseSX ports (multi-mode SC connector)- 1Magnetic isolation protection- 1.5 kV (built-in) Performance parameters Input current- 284.7 mA @ 12 to 48 VDC Input voltage- 12 to 48 VDC Overload current protection- Supported Power connection- Terminal block Power consumption- 284.7 mA @ 12 to 48 VDC Physical Characteristics Housing- Metal Dimensions- 30 x 125 x 79 mm (1.19 x 4.92 x 3.11 in) Weight- 170 g (0.37 lb) Installation- DIN rail mounting Ambient conditions Operating temperature- -10 to 60°C (14 to 140°F) Storage temperature (including packaging)- -40 to 75°C (-40 to 167°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/24 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m- IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV- IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Environmental testing- IEC 60068-2-1- IEC 60068-2-2- IEC 60068-2-3 Safety- EN 60950-1, UL 60950-1 Vibration- IEC 60068-2-6 MTBF Time- 2.762,058 hours Standards- MIL-HDBK-217F

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

