

Item no.: 386085

IMC-21GA-LX-SC-T - Industrial 101001000BaseT(X) to 1001000Base SC media converter

from **476,24 EUR**

Item no.: 386085
shipping weight: 0.30 kg
Manufacturer: MOXA



Product Description

Moxa's Ethernet to Fiber media converters feature innovative remote management, industrial-grade reliability, and a flexible, modular design that can fit any type of industrial environment. Industrial 10/100/1000BaseT(X) to 100/1000Base SC media converter, 10 km, -40 to 75°C operating temperature. Ethernet Interface- 10/100/1000BaseT(X) Ports (RJ45 connector) 1- 1000BaseLX Ports (single-mode SC connector) 1- Magnetic Isolation Protection 1.5 kV (built-in) Power Parameters- Input Current 284.7 mA @ 12 to 48 VDC- Input Voltage 12 to 48 VDC- Overload Current Protection Supported- Power Connector Terminal block- Power Consumption 284.7 mA @ 12 to 48 VDC Physical Characteristics- Housing Metal- Dimensions 30 x 125 x 79 mm (1.19 x 4.92 x 3.11 in)- Weight 170 g (0.37 lb)- Installation DIN-rail mounting Environmental Limits- Operating Temperature -40 to 75°C (-40 to 167°F)- Storage Temperature (package included) -40 to 75°C (-40 to 167°F)- Ambient Relative Humidity 5 to 95% (non-condensing) Standards and Certifications- EMC EN 55032/24- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; Signal: 10 V/m IEC 61000-4-8 PFM IEC 61000-4-11- Environmental Testing IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-3- Safety EN 60950-1, UL 60950-1- Vibration IEC 60068-2-6 MTBF- Time 2,762,058 hrs- Standards MIL-HDBK-217F

Specifications

Scan this QR code to
view the product

All details, up-to-date
prices and availability

