

Item no.: 386071

IMC-101-S-SC - Industrial 10/100BaseT(X) to 100BaseFX media converter, single-mode, SC fibre con

from **361,06 EUR**

Item no.: 386071
shipping weight: 0.30 kg
Manufacturer: MOXA



Product Description

Industrial 10/100BaseT(X) to 100BaseFX media converter, singlemode, SC fibre optic connection, 40 km, 0 to 60 °C operating temperature Ethernet interface- 10/100BaseT(X) ports (RJ45 connection):1- 100BaseFX ports (singlemode SC connector): 1- Magnetic isolation protection: 1.5 kV (built-in) Performance parameters- Input current: 200 mA at 12 to 45 VDC- Input voltage:12 to 45 VDC- Overload current protection: Supported- Connector: Terminal block- Power consumption: 200 mA at 12 to 45 VDC Physical characteristics- IP rating: IP30- Housing: Metal- Dimensions: 53.6 x 135 x 105 mm (2.11 x 5.31 x 4.13 inches)- Weight: 630 g (1.39 pounds)- Installation: DIN rail mount Environmental limits- Operating temperature: 0 to 60 °C (32 to 140 °F)- Storage temperature (included): -40 to 85 °C (-40 to 185 °F)- Ambient relative humidity: 5 to 95 % (non-condensing) Standards and certifications- EMC: EN 55032/24- EMI: CISPR 32, FCC Part 15B Class A- EMS: IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV; Signal: 1 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m IEC 61000-4-8 PFM IEC 61000-4-11- Environmental testing IEC 60068-2-1 IEC 60068-2-2 IEC 60068-2-3- Safety: EN 60950-1, UL 60950-1- Vibration: IEC 60068-2-6- Hazardous locations: ATEX Zone 2, UL/cUL Class I Division 2 Groups A/B/C/D- Maritime: DNVMTBF- Time: 401.000 hours- Standards: MIL-HDBK-217F

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

