

Item no.: 386082

IMC-21A-S-SC-T - Industrial 10/100BaseT(X) to 100BaseFX media converter, singlemode

from **324,96 EUR**

Item no.: 386082
 shipping weight: 0.30 kg
 Manufacturer: MOXA



Product Description

Industrial 10/100BaseT(X) to 100BaseFX media converter, singlemode, SC fibre optic connector, -40 to 75°C Operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector)- 1100BaseFX ports (singlemode SC connector)- 1Magnetic isolation protection- 1.5 kV (built-in) Performance parameters Input current- 12 to 48 VDC, 265mA (Max.) Input voltage- 12 to 48 VDC Overload current protection- Supported Mains connection- Terminal block Reverse polarity protection- Supported Physical properties Housing- Metall IP protection class- IP30 Dimensions- 30 x 125 x 79 mm (1.19 x 4.92 x 3.11 in) Weight- 170 g (0.37 lb) Installation- DIN rail mounting Ambient conditions Operating temperature- -40 to 75°C (-40 to 167°F) Storage temperature (including packaging)- -40 to 75°C (-40 to 167°F) -40 to 75°C (-40 to 167°F) Relative humidity- 5 to 95% (non-condensing) Standards and certifications EMC- EN 55032/24 EMI- CISPR 32, FCC Part 15B Class A EMS- IEC 61000-4-2 ESD: Contact: 6 kV; air: 8 kV- IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m- IEC 61000-4-4 EFT: Power: 1 kV; signal: 0.5 kV- IEC 61000-4-5 Surge: Power: 1 kV; signal: 1 kV- IEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; Signal: 3 V/m- IEC 61000-4-8 PFMF- IEC 61000-4-11 Environmental testing- IEC 60068-2-1- IEC 60068-2-2- IEC 60068-2-3 Safety- EN 60950-1, UL 60950-1 Vibration- IEC 60068-2-6 MTBF Time- 353.000 hours Standards- MIL-HDBK-217F

Specifications

Scan this QR code to
 view the product
 All details, up-to-date
 prices and availability

