

Item no.: 386147

ICF-1150I-S-SC-T - Industrial RS-232/422/485 to single-mode fibre optic converter, SC connector

from **706,75 EUR**

Item no.: 386147
shipping weight: 0.30 kg
Manufacturer: MOXA



Product Description

Industrial RS-232/422/485 to single-mode fibre optic converter, SC connector, 2 kV insulation, -40 to 85°C operating temperature
Serial interface-Number of ports:2-Serial standards: RS-232, RS-422, RS-485-Baud rate:50 bps to 921.6 kbps (supports non-standard baud rates)-Flow Control:ADDC (automatic data direction control) for RS-485-Connector: 5-pin terminal block, single-mode SC connector-Insulation: 2 kV (I models)-Optical fibre-Pull high/low resistance for RS-485: 150 kilo-ohms, 10 kilo-ohms, 4.7 kilo-ohms, 3.3 kilo-ohms, 1 kilo-ohm, 909 ohms, 822 ohms, 770 ohms, 500 ohms, 485 ohms-RS-485 data direction control: ADDC (automatic data direction control)-Terminator for RS-485:N/A, 120 ohms, 120 kilo-ohmsSerial signals-RS-232: Tx+, Tx-, Rx+, Rx-, GND-RS-422: Tx+, Tx-, Rx+, Rx-, GND-RS-485-4w: Tx+, Tx-, Rx+, Rx-, GND-RS-485-2w: Data+, Data-, GNDPerformance parameters-Input current: 300 mA @ 12 to 48 VDC-Input voltage: 12 to 48 VDC-Number of power inputs: 1-Overload protection: Supported-Current connection: terminal block-Current consumption: 300 mA @ 12 to 48 VDCPhysical characteristics-Casing: metal-IP rating: IP30-Dimensions: 30.3 x 70 x 115 mm (1.19 x 2.76 x 4.53 in)-Weight: 330 g (0.73 lb)-Installation: DIN rail mountingEnvironmental Conditions-Operating Temperature: -40 to 85°C (-40 to 185°F)-Storage Temperature (including packaging): -40 to 85°C (-40 to 185°F)-relative humidity: 5 to 95% (non-condensing)Standards and certifications-EMC: EN 55032/35-EMI: CISPR 32, FCC Part 15B Class A-EMS:IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kVIEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/mIEC 61000-4-4 EFT: Power: 4 kV; Signal: 2 kVIEC 61000-4-5 Surge: Power: 4 kV; Signal: 1 kVIEC 61000-4-6 CS: 150 kHz to 80 MHz: 3 V/m; signal: 3 V/mIEC 61000-4-8 PFMF-Environmental testing:IEC 60068-2-1IEC 60068-2-2IEC 60068-2-3-Safety: UL 61010-2-201-Vibration: IEC 60068-2-6-Hazardous areas: UL/cUL Class I Division 2 Groups A/B/C/D, ATEX Zone 2MTBF-Time: 792,085 hours-Standards: Telcordia (Bellcore), GB

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

