

Item no.: 386194

## PTC-101-M-ST-HV - Industrial 10/100BaseT(X) to 100BaseFX media converter

from **503,03 EUR**

Item no.: 386194  
shipping weight: 0.30 kg  
Manufacturer: MOXA



### Product Description

Industrial 10/100BaseT(X) to 100BaseFX media converter, multimode with ST connector, 1 isolated power supply (88 to 300 VDC or 85 to 264 VAC), -40 to 85 °C operating temperature Ethernet interface 10/100BaseT(X) ports (RJ45 connector): 1 100BaseFX ports (multimode ST connector): 1 Magnetic isolation protection: 1.5 kV (built-in) Performance parameters-Input voltage: 100 to 240 VAC, 100 to 240 VDC-Input current: 350 to 200 mA at 100 to 240 VAC 350 to 200 mA at 100 to 240 VDC-Overload current protection: Supported-Energy consumption: 350 to 200 mA at 100 to 240 VAC 350 to 200 mA at 100 to 240 VDC Physical characteristics-Casing: metal-Dimensions: 152.15 x 126.46 x 66.65 mm (5.99 x 4.86 x 2.62 in.)-Weight: Packaged: 952 g (2.09 lb) Product only: 785 g (1.73 lb)-Installation: DIN rail mounting Environmental limits Operating temperature: -40 to 85 °C (-40 to 185 °F) Storage temperature (included): -40 to 85 °C (-40 to 185 °F) Ambient relative humidity: 5 to 95 % (non-condensing) Standards and certifications-EMC: EN 55032/35-EMI: CISPR 32, FCC Part 15B Class A-WMS: IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 4 kV; Signal: 4 kV IEC 61000-4-5 Overvoltage: power: 4 kV; signal: 4 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m; signal: 10 V/m IEC 61000-4-8 PFM IEC 61000-4-11 Environmental tests: IEC 60068-2-1 IEC 60068-2-14 IEC 60068-2-2 IEC 60068-2-3 Safety: EN 62368-1, UL 62368-1, UL 60950-1-Vibration: IEC 60068-2-6-Substation: IEC 61850-3 MTBF Time: 4.660,534 hrs Standards: Telcordia SR332

### Specifications

Scan this QR code to  
view the product

All details, up-to-date  
prices and availability

