

Item no.: 374927

TAPO C211 - Schwenk-/Neigbare Wi-Fi-Kamera für die Heimüberwachung

from **44,07 EUR**

Item no.: 374927
shipping weight: 0.50 kg
Manufacturer: TP-LINK



Product Description

KAMERA- Bildsensor 1/2.8"- Linse F/NO: 2.4; Focal Length: 3.83mm- Motion Range Pan Mechanical Range: 340° (360° Pan Coverage)- Tilt Mechanical Range: 70° (116.65° Tilt Coverage)- Night Vision 850 nm IR LED up to 30 ft- Lighting / Interface & Button 1x RESET Button- 1x MicroSD Card Slot (Up to 512 GB)- Hub Compatibility / View Range 360° horizontal, 114° vertical- Auflösung 3MP(2304 x 1296)HUB- Device Compatibility /- Connection Capacity /- Interface & Button /VIDEO & AUDIO- Maximum Resolution 2K 3MP (2304 x 1296 px)- Frame Rate 15/20/25/30 fps (Default 15 fps, can be set up to 30 fps)- Digital Zoom None- Video Compression H.264/H.265- Live View Yes- Image Enhancement 3D DNR WDR- Audio Input & Output Built-in Microphone and Speaker- Audio Communication Two-Way Audio with Noise Cancellation- Siren Volume 88dB (Level measured at 4-inch/10-cm distance)STORAGE- Local Storage MicroSD Card Slot on Camera (Up to 512 GB)- General Information about using MicroSD Cards >- Cloud Storage Tapo Care Cloud Storage Services (Subscription required)VIDEO- Frame Rate 15fps- Video Streaming 3MP- Video Compression H.264DETECTION AND NOTIFICATIONS- Sensor /- AI Detection Motion Detection- Person Detection- BabyCry Detection - Activity Zones Yes- Output Notification System Notification- System Notification with Snapshot (Tapo Care Services)AUDIO- Audiokommunikation 2-way audio- Audio Input & Output Built-in microphone and speakerNETZ- Network Connectivity Connect via Wi-Fi or Ethernet cable- Wireless Connectivity IEEE 802.11b/g/n, 2.4 GHz Wi-Fi- Wireless Rate 11Mbps(802.11b), 54Mbps(802.11g), 72.2Mbps(802.11n)- Ethernet Port 1x 100 Mbps RJ45 Port on Camera- Wireless Security WPA/WPA2-PSK- RTSP Yes- ONVIF Yes- Sicherheit 128 bit AES encryption with SSL/TLS- Frequency 2.4 GHzSICHERHEIT -Security On-Device Machine Learning- 128-bit AES Encryption with SSL/TLS- WPA/WPA2-PSK POWER- Power Source 9V DC Power Adapter - Input Voltage 100-240 V, 50/60 Hz - Output Voltage DC9.0V/0.6A(DC Power) ALLGEMEIN- Smart Integration Google Assistant, Amazon Alexa - Weather Resistance /- System Requirements Tapo App: iOS 9.0 or higher, Android 4.4 or higher - Mounting Options Tabletop- Ceiling-Mounted - Operating Temperature 0°-40° - Storage Temperature -20°-70° - Operating Humidity 10%-90% RH, Non-condensing - Storage Humidity 5%-90% RH, Non-condensing - Charging Temperature /- Dimensions 3.36 x 3.42 x 4.63 in (85.4 x 86.8 x 117.7 mm) - Verpackungsinhalt Tapo C211 Kamera- Power Adapter- Quick Start Guide- Mounting Screws- Mounting Anchors - Mounting Template- Camera Base- Certifications /ACTIVITY NOTIFICATIONS- Input Trigger Motion detection- Output Notification Push notificationSYSTEM- Regulatory Certification CE, NCC- System Requirements iOS 10+, Android 5.0+ENVIRONMENT- Operating Temperature 0°C~40°C (32°F~104°F)- Storage Temperature -40°C~70°C (-40°F~158°F)- Operating Humidity 10%-90%RH non-condensing- Storage Humidity 5%-90%RH non-condensingPACKAGE CONTENTS- Package Contents Tapo Pan/Tilt Home Security Wi-Fi Camera- Power Adapter- Quick Start Guide- Mounting Screws- Mounting Plate- Camera BaseHARDWARE- Button Reset button- Indicator LED System LED- Adapter Input 100-240VAC, 50/60Hz, 0.3A- Adapter Output 9.0V/0.6A- Power 3.4 x 3.3 x 4.6 in. (86.6 x 85 x 117.7 mm)- Dimensions (W x D x H) 3 Meter Power Cable

Specifications

Scan this QR code to
view the product
All details, up-to-date
prices and availability

