

Item no.: 385428

## UPOINT 404A-T - 4-port industrial-grade USB 3.2 hubs, -40 to 85C operating temperature

from **310,64 EUR**

Item no.: 385428  
 shipping weight: 0.20 kg  
 Manufacturer: MOXA



### Product Description

The UPort series of USB hubs is industrial-grade and designed with the ruggedness and reliability needed for industrial applications. Each port has ESD Level 4 protection and provides Super-Speed USB 3.2 data rates up to 5 Gbps—even for heavy-load applications. The UPort Series includes models with dual power inputs, DIN-rail mounting options, and wide temperature models that operate reliably even in harsh conditions.

**4-port industrial-grade USB 3.2 hubs, -40 to 85°C operating temperature**

**USB Interface- USB Standards** USB 3.2 Gen 1 USB 1.1/2.0 compliant- Speed 5 Gbps- USB Connector UFP: type B DFP: type A- No. of USB Ports 5 (UFP: 1, DFP 4)

**Power Parameters- Input Voltage** 12 to 48 VDC

**No. of power inputs:** 2- Power Connector Power jack 3-pin terminal block- Reverse Polarity Protection Supported- Input Current 2..8 A @ 12 VDC- Output Power Rating

**Port 1:** 900 mA / 1500 mA @ 5 VDC, BC 1.2 compliant

**Rest of ports:** 900 mA @ 5 VDC

**Physical Characteristics- Housing** Metal- Dimensions 85 x 27 x 100 mm (3.35 x 1.06 x 3.94 in)- Weight 264 g (0.58 lb)- Installation Wall mounting (with optional kit) DIN-rail mounting (with optional kit)

**Environmental Limits- Operating Temperature** -40 to 85°C (-40 to 185°F)- Storage Temperature (package included) -40 to 85°C (-40 to 185°F)- Ambient Relative Humidity 5 to 95% (non-condensing)

**Standards and Certifications- EMC** EN 55032/35- EMI CISPR 32, FCC Part 15B Class A- EMS IEC 61000-4-2 ESD: Contact: 8 kV; Air: 15 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 10 V/m IEC 61000-4-4 EFT: Power: 2 kV IEC 61000-4-5 Surge: Power: 2 kV IEC 61000-4-6 CS: 150 kHz to 80 MHz: 10 V/m IEC 61000-4-8 PFMF- Safety EN 62368-1 UL 62368-1 KC- Environmental Testing IEC 60068-2-1- Freefall IEC 60068-2-34

**Declaration- Green Product** RoHS, CRoHS, WEEE MTBF- Standards Telcordia (Bellcore), GB- Time 2,107,973 hrs

### Specifications

Scan this QR code to view the product  
 All details, up-to-date prices and availability

